

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NW 1/4 NE 1/4 SE 1/4	26	T 27 S	R 2 E
Distance and direction from nearest town or city street address of well if located within city? 14135 Spring Valley, Wichita, KS					
2 WATER WELL OWNER: Wayne Bell		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 14135 Spring Valley		Application Number:			
City, State, ZIP Code: Wichita, KS					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 93 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm; Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 10 5/8 in. to 93 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☒ No ☐			
5 TYPE OF BLANK CASING USED:					
1 Steel		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped	
3 RMP (SR)		6 Asbestos-Cement	9 Other (specify below)	Welded	
2 PVC		7 Fiberglass		Threaded	
4 ABS					
Blank casing diameter 6" in. to 2 ft. Dia 5 in. to 93 ft. Dia in. to ft.					
Casing height above land surface 18 in. weight Sch 26 lbs./ft. Wall thickness or gauge No. Sch 26					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		5 Fiberglass	8 RMP (SR)	10 Asbestos-cement	
3 Stainless steel		6 Concrete tile	9 ABS	11 Other (specify)	
2 Brass				12 None used (open hole)	
4 Galvanized steel					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
3 Mill slot		6 Wire wrapped	9 Drilled holes		
2 Louvered shutter		7 Torch cut	10 Other (specify)		
4 Key punched					
SCREEN-PERFORATED INTERVALS: From 73 ft. to 93 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 22 ft. to 93 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 2 ft. to 22 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		7 Pit privy	10 Livestock pens	14 Abandoned water well	
4 Lateral lines		8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
2 Sewer lines		9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
3 Watertight sewer lines			13 Insecticide storage		
6 Seepage pit					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil	87	93	Shale
2	18	Brown Clay			
18	21	Broken Lime			
21	25	Brown Clay			
25	26	Broken Lime			
26	28	Clay/Sandy Shale			
28	29	Lime			
29	45	Clay/Sandy Shale			
45	48	Broken Lime			
48	50	Hard Lime			
50	64	Gray Shale			
64	66	Hard Shale			
66	72	Lime			
72	85	Shale			
85	87	Lime			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-20-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 464 This Water Well Record was completed on (mo/day/yr) 5-20-98 under the business name of Water Well Services by (signature) <i>[Signature]</i>					