1 LOCATION OF WATER WELL:		FRACTION	. W	ater well kee	cora Form v	vwc-s	Section Number	Township Number	Panes Number	
Sedgwick		SW 1/4	NW	1/4	CTAT	1/4	i	1	Range Number	
Distance and direction from nearest town or city street address of well if loc				1/4	SW	1/4	11	T 27 s	R 2E E/W	
	5 Rocky Creek			Wich	<u>nita,</u>	<u>Ka</u>	nsas	w 		
	DICONIA	, Reff	. 1					Deced of Academistrate D	· · · · · · · · · · · · · · · · · · ·	
		Rocky Cr							ivivsion of Water Resource	
$\overline{}$		ta, Kans							r:	
	WELL'S LOCATION WITH SECTION BOX:	DEPTH OF CO			_	0		VATION:		
٦ ، ١	N	lwater End				ft.	2 ft.	3 ft.		
	W	ELL'S STATIC						RFACE MEASURED ON mo/day/yr	07/08/1999	
'	NWNE	-	est data:		ll water wa			after hours pum		
<u> </u>		t. Yield	gpm:		ll water w			after hours pum		
M Mile		re Hole Diameter			to 7		ft.	and in.	to ft.	
L	z "'	ELL WATER TO	BE USEI 3 Feed		5 Public			•	njection weli	
'	swsæ	1 Domestic 2 Irrigation		giot ustrial					Other (Specify below)	
	l l w						·	0 Monitoring weli		
' -		as a chemical/bac ubmitted	teriologica	al sampie	submittea	to D	_		o/day/yr sample was	
5 TYPE	OF CASING USED:	1bmittea				_		er Well Disinfected? Yes	48	
1 Steel	3 RMP (SR)			ought iro estos-Cen		-	Concrete tile		lued X Clamped	
2 PVC	4 ABS			estos-Cen erglass	neni		Other (Specify be	•	Velded breeded	
		4. 25		•			DR-26		hreaded	
	ng Diameter 5 in. ght above land surface 12		ft.,		2 25	in.	to	ft., Dia in.	to ft.	
	SCREEN OR PERFORATIO	in. :N MATERIAL	,	weight	2.35	7	lbs. / ft. V 7 PVC	Wall thickness or gauge No. 10 Asbestos-ceme	.214	
1 Steel	3 Stainless Steel	IN INTERIOR	5 Flber	rglass			RMP (SR)	11 other (specify)		
2 Brass	4 Galvanized steel			rete tile			O ABS	12 None used (op		
	OR PERFORATION OPENI	NC ADE.	-		J		ADS	8 Saw cut	en noie) 11 None (open hole)	
1 Continou		NG ARE:		S Gauzeu wrappeu					9 Drilled holes	
2 Louvered	5 Will sitt	hed				•				
/ Torch cut										
SCREEN-1	ERIORATION INTERVAL	J	5		ft. to 70		ft., From	ft. to	ft.	
from GRAVEL PACK INTERVALS: from 24				ft. to			ft., From	ft. to	ft.	
· '	GRAVEL FACK INTERVAL	LS: 110m ∠ from	4		ft. to 70	,	ft., From ft., From		ft.	
from ft. to ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other										
		t. to 24	-	From	·	ft.				
What is the nearest source of possible contamination:			14-	ic riom			10 Livestoc	ft. From k pens 14 A	ft. to ft. bandon water well	
1 Septic tank 4 Lateral lines			7	7 Pit privy			11 Fuel sto		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 9	8 Sewage lagoon			12 Fertilize		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage								(1)		
Direction from well? East How many feet? 100										
	TO LIT	HOLOGIC LOG	ř		FRO	OM	то	PLUGGING INTER	VALS	
0 3	topsoil									
3 1		***************************************								
11 2										
21 4		}								
49 5										
53 6:		<u> </u>								
63 7	0 limestone									
							 			
		1								
-										
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and										
was completed on (mo/day/year)										
Well Contractor's License No236										
Under the business name of HarpWell& PumpServiceInc by (signature)										
								Joaa D	. Harb	