

1

LOCATION OF WATER WELL:

County:

Sedgwick

2

Fraction

SE 1/4 NW SE 1/4 SE 1/4

3

Section Number

13

4

Township Number

T 27 S

5

Range Number

R 2E EW

Distance and direction from nearest town or city street address of well if located within city?

564 Brookhaven, Wichita, KS 67230

6

WATER WELL OWNER:

Kevin REiboldt

RR#, St. Address, Box # :

564 Brookhaven

City, State, ZIP Code :

Wichita, KS 67230

Board of Agriculture, Division of Water Resources

Application Number:

7

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

8

DEPTH OF COMPLETED WELL:

80

ft. ELEVATION:

Depth(s) Groundwater Encountered

1.

ft.

2.

ft.

3.

ft.

WELL'S STATIC WATER LEVEL

12

ft. below land surface measured on

mo/day/yr

7/30/99

Pump test data:

Well water was

ft. after

hours pumping

gpm

Est. Yield

gpm:

Well water was

ft. after

hours pumping

gpm

Bore Hole Diameter

9.

in. to

80

ft., and

in. to

ft.

WELL WATER TO BE USED AS:

5 Public water supply

8 Air conditioning

11 Injection well

1 Domestic

3 Feedlot

6 Oil field water supply

9 Dewatering

12 Other (Specify below)

2 Irrigation

4 Industrial

7 Lawn and garden only

10 Monitoring well

Was a chemical/bacteriological sample submitted to Department?

Yes

No

X

If yes, mo/day/yr sample was submitted

Water Well Disinfected?

Yes

No

X

9

TYPE OF BLANK CASING USED:

1 Steel

3 RMP (SR)

5 Wrought iron

8 Concrete tile

CASING JOINTS:

Glued

X

Clamped

2 PVC

4 ABS

6 Asbestos-Cement

9 Other (specify below)

Welded

Blank casing diameter

5

in. to

60

ft., Dia

in. to

ft., Dia

in. to

ft.

Casing height above land surface

12

in., weight

lbs./ft. Wall thickness or gauge No.

SDR26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

8 RMP (SR)

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

9 ABS

11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS:

From

60

ft. to

80

ft., From

ft. to

ft.

GRAVEL PACK INTERVALS:

From

20

ft. to

80

ft., From

ft. to

ft.

10

GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals:

From

4

ft. to

20

ft., From

ft. to

ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

How many feet?

FROM

TO

LITHOLOGIC LOG

FROM

TO

PLUGGING INTERVALS

0

12

Soil & Clay

12

20

Lime

20

35

Shale

35

65

Lime

65

85

Lime w/Shale stks.

11

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:

This water well was

1

constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

completed on (mo/day/year)

7/30/99

and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No.

171

This Water Well Record was completed on (mo/day/yr)

8/2/99

under the business name of

G&S Drilling, Inc.

by (signature)

INSTRUCTIONS:

Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.