


1 LOCATION OF WATER WELL: Sedgwick	FRACTION 1/4 1/4 SW 1/4	Section Number 10	Township Number T 27 S	Range Number R 2E E/W
--	----------------------------	-----------------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

107'S. & 452' W. of NE corner Wichita, Kansas

WATER WELL OWNER: CHAPEL HILL FELLOWSHIP UNITED METHODIST CHURCH	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: 9431 E. Central Ave, Suite 300	Application Number:
CITY, STATE, ZIP CODE: Wichita, Kansas	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 73 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 30.5 FT. BELOW LAND SURFACE MEASURED ON 08/05/1999 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 20 ft. and 9 7/8" in. to 74 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well test well 1-99 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No
--	---

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing Diameter 5 in. to 53 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 21 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATION INTERVALS: from 53 ft. to 73 ft., From ft. to ft. GRAVEL PACK INTERVALS: from 39 ft. to 73 ft., From ft. to ft.	CASING JOINTS: Glued Clamped Welded Threaded
--	--

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug Grout Intervals: From ft. to ft. From ft. to ft. From 0 ft. to 39 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent Direction from well? How many feet?
--

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	topsoil & clay, silty, dark gray- brown	64	74	shale, (wea. Wellington), gray-brown to dark-black-gray
5	21	clay, silty, light brown tan to yellow tan white with hard streaks	74		limestone, off-white
21	25	clay, silty, light maroon			
25	35	clay, silty, off white w/ thin streaks of brown ls.			
35	40	clay, silty, light gray			
40	54	clay, silty, light gray to light brown gray with hard streaks			
54	64	shale, (wea. Wellington), dark- black- gray to green gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/26/1999 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 08/20/99 Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp
