1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number		T
	. 1	GT4 GT				Range Number
Sedgwick Distance and direction from peacest town or or	NE NE 1/4	SW 1/4 ST	1/4	7	т 27 в	R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?						
6613 Abbotsford Place Wichita, Kansas Water Well OWNER: PARKS, Herman						
	3 Abbotsfor	d Dlace			Board of Agriculture, D	ivivsion of Water Resource
	hita, Kansa				Application Number	
LOCATE WELL'S LOCATION WITH		PACE WELL	27	ft. E	LEVATION:	•
AN "X" IN SECTION BOX:	Depth(s) groundw		1	ft.	2 ft.	3 ft.
1 1 1	WELL'S STATIC W	ATER LEVEL 11	FT.	BELOW LAND	SURFACE MEASURED ON mo/day/yr	10/27/1999
NWNE	Pump tes		iter was	ft.	after hours pum	
	Est. Yield	gpm: Well w	ater was	ft.	after hours pum	
W W	Bore Hole Diameter	in. t	0	ft.	and in.	to ft.
= "	WELL WATER	E USED AS: 5	Public water	supply	8 Air conditioning 11 Is	njection well
75W	1 Domestic		Oil field wat	er supply	9 Dewatering 12 C	Other (Specify below)
	2 Irrigation	4 Industrial 7	Lawn and ga	rden only	10 Monitoring well	
		eriological sample sub	mitted to Dep			o/day/yr sample was
submitted water weit Disinfected: Yes X No						
5 TYPE OF CASING USED:		5 Wrought iron	-	Concrete tile		lued Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Cement	9 (Other (Specify		/elded
2 PVC 4 ABS		7 Fiberglass			_	hreaded
Blank casing Diameter 6	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height to land surface TYPE OF SCREEN OR PERFORA		weight		lbs. / ft. PVC	Wall thickness or gauge No. 10 As bestos-ceme	ent
1 Start 2 Statute Start 5 Fibergloss 9 DMD (SD) 14 db (context)						
2 Brass 4 Galvanized st		6 Concrete tile		ABS	12 None used (op	M/A
SCREEN OR PERFORATION OF	5 Gauze			8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill slot		5 Gauzed wrapped 6 Wire wrapped			9 Drilled holes	
2 Louvered shutter 4 Key	7 Torch			10 Other (specify) N	/ A	
SCREEN-PERFORATION INTER	•	ft. t		ft., Fr	11 21/	ft.
	from	ft. í	_			ft.
GRAVEL PACK INTER		ft.	-	ft., Fr ft., Fr		ft.
	from	ft. f		ft., Fr		ft.
6 GROUT MATERIAL: 1 Near	cement 2 (Cement grout	3 Bent	tonite	4 Other bentonite	hole plug
Grout Intervals: From 3 ft. to 9		ft. From ft. to		0	ft. From 9 ft. to 11 ft.	
What is the nearest source of possible contamination:					restock pens 14 Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy				Dil well/Gas well
2 Sewer lines 5 Cess pool		6 6			ertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Fe			13 Insecticide storage None Apparent			
Direction from well? How many feet? FROM TO PLUGGING INTERVALS						
FROM 10	LITHOLOGIC LOG		FROM 0	3	PLUGGING INTER	
			3	9	cement grout	G BIIC
			9	11	bentonite hole	nlua
			11	27	chlorinated san	
7 CONTRACTOR'S OR LANDOWN	er's certification: Th	is water well was (1)	constructe	d, (2) recons	structed, or (3) plugged under n	ny jurisdiction and
was completed on (mo/day/yea	r) 10/27/	1999	nd this rec	ord is true to	the best of my knowledge and	belief. Kansas Water
was completed on (mo/day/yea Well Contractor's License No	r) 10/27/ 236	1999 This Water Well Re	ind this reco	ord is true to empleted on	the best of my knowledge and (mo/day/yr)10./.29	belief. Kansas Water
was completed on (mo/day/yea	r) 10/27/ 236	1999 This Water Well Re	ind this reco	ord is true to empleted on	the best of my knowledge and (mo/day/yr)10./.29	belief. Kansas Water