

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction: C 1/4 NW 1/4 NW 1/4		Section Number: 24		Township Number: T 27 S		Range Number: R 2 E	
Distance and direction from nearest town or city street address of well if located within city? #6 Scottsdale, Wichita, KS 67230									
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Rosco Mendenhall #6 Scottsdale Wichita, KS 67230				Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on mo/day/yr 2/15/00 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 88 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped Welded Threaded					
Blank casing diameter 5 in. to 68 ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface 12 in. weight lbs./ft. Wall thickness or gauge No. SDR26							
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		7 PVC 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 68 ft. to 88 ft. From ft. to ft. From ft. to ft. From ft. to ft.		GRAVEL PACK INTERVALS: From 20 ft. to 88 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 4 ft. to 20 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage		Direction from well? How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 24 Clay									
24 34 Shale									
34 37 Lime									
37 48 Shale									
48 64 Shale & Lime									
64 88 Cherty Lime									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/15/00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 171 This Water Well Record was completed on (mo/day/yr) 2/24/00 under the business name of G&S Drilling, Inc. by (signature) Timothy E. Brandt									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									