LILOCA	TION OF W	ATER WELL:	Т	FRACTION	v	Vater Well Red	cord Form WWC			T				
LILOCA			l				<b>~-</b> -	Section Nur	mber	Township Nu	mber	Range Numi	per	
Sedgwick SW 1/4						1/4	SW 1/4	1/4 11		<sub>T</sub> 27 <sub>s</sub>		R 2E E/W		
Distance and direction frem nearest town or city street address of well if located within city?														
		Castlewoo				Wic	<u>chita, F</u>	ansas						
ш	TER WELL (	+ 1110	_	C.T.						Pene	d of Assisulture Di	whiches of Water Dane		
RR#, ST. ADRESS, BOX#: 13211 Castelwood CITY, STATE, ZIP CODE: Wichita, Kansas							Board of Agriculture, Divivsion of V						arce	
											Application Number	:		
	TE WELL'S L " IN SECTIO	OCATION WITH N BOX:		EPTH OF C				ft.	ELEV	VATION:	~	2		
l ,	- :	N	1	epth(s) groun				ft.	un eun	2 FACE MEASURED	ft.	3	ft.	
			WEL	L'S STATIC	test data:		-					07/05/2		
'	··-·· <b>NW</b> ·	NE	Est. Y	-			ll water was ll water was			fter	hours pum		gpm	
M Mile		_		rieiu Hole Diamet	gpm: er 12		to 80	ſ		ifter	hours pum		gpm ft.	
ĭ≅w		E	1	L WATER T			5 Public wate			and Air conditionin	in. a 11 Ir	to ijection well	It.	
				Domestic	3 Fee		6 Oil field w			Dewatering	•	ther (Specify bel	ow)	
Sw SE 2 Irrigation						4 Industrial 7 Lawn and garden only 10 Monitoring well								
							ical sample submitted to Department? Yes  No X; If yes, mo/day/yr sample was							
S submitted										Water Well Disinfected? Yes X No				
5 TY	PE OF CA	SING USED:			5 W	rought iro	n	8 Concrete ti	ile	CASING J	OINTS: G	ued X Clamp	ed	
1 Stee	l	3 RMP (SR)				bestos-Cer		Other (Spe		low)		elded	_	
2 PVC	2	4 ABS			7 Fib	erglass		DR-26	•	,	T	hreaded		
Blank ca	_ ising Diam	eter 5	in.	to 40	ft.,	Dia	in	. to		ft., Dia	in.	to f	t.	
			12		և,		2.35	lbs. / ft.		Vall thickness or	gauge No.	.214		
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement														
1 Stee		3 Stainless Steel			5 Fibe	-		8 RMP (SR)		11	other (specify)	1		
2 Brass 4 Galvanized steel 6 Concrete								9 ABS			None used (op	en hole)		
							auzed wrapped			8 Saw cut		11 None (oper	ı hole)	
l .	nous slot	3 Mill s				6 Wi	ire wrapped			9 Drilled hole				
1	red shutte			l		7 To	rch cut			10 Other (sp	ecify)			
SCREE	N-PERFO	RATION INTER	VALS:	from 4	10		ft. to 80	ft.,	From		ft. to		ft.	
from							ft. to	ft., Fro					ſt.	
GRAVEL PACK INTERVALS: from 24					24		ft. to 80	,			ft. to		ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout													<u>ft.</u>	
Grout Intervals: From ft. to											bentonite hole plug			
What is the nearest source of possible contamination:					It.	From	ft.	ft. to 10 Lives		ft. From 4 stock pens 1		ft. to 24 ft. Abandon water well		
1 Septic tank 4 Lateral lines						7 Pit privy	7		uel stor	•		il well/Gas well	п	
2 Sewer lines 5 Cess pool					8	Sewage la	igoon			er storage		ther (specify belo	ow)	
3 Watertight sewer lines 6 Seepage pit						Feedyard	l	13 Insecticide storage						
Directio	n from wel		B- F			-				How many fo	et? 20			
FROM TO LITHOLOGIC LOG						FROM TO			PLUGGING INTERV			VALS		
0	4	topsoil												
4	15	clay												
15	80	shale							+					
									+					
									+					
									+					
							<del>-  </del>				VIA.			
								1						
										1.00				
7 CO	NTRACTO	R'S or landowne	R'S CFE	TIFICATION:	This wate	r well was	s (1) construc	ted. (2) reco	onstru	cted, or (3) plu	aged under m	v jurisdiction a	ınd	
Was c	ompleted	on (mo/day/year	r)	07/05	/00		and this re	cord is true	to the	best of my kn	owledge and	belief. Kansas	Water	
Well C	ontractor	's License No	23	6	This W	ater Well	Record was	completed o	on (mo	/day/yr)	07/07	//00		
		ness name of.Hi										_		
											Todd S	. литр		