

1 LOCATION OF WATER WELL: Sedgwick		FRACTION SW 1/4 NW 1/4 NE 1/4		Section Number 24		Township Number T 27 S		Range Number R 2E E/W	
Distance and direction from nearest town or city street address of well if located within city? 4950 Windham Ct. Wichita, Kansas									
WATER WELL OWNER: YOUNG, Walter					Board of Agriculture, Division of Water Resource				
RR#, ST. ADDRESS, BOX #: 4950 Windham Ct.					Application Number:				
CITY, STATE, ZIP CODE: Wichita, Kansas									
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 50 ft. ELEVATION:							
		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.							
		WELL'S STATIC WATER LEVEL 6 FT. BELOW LAND SURFACE MEASURED ON 08/08/2000							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
Bore Hole Diameter 12 in. to 50 ft. and in. to ft.									
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes ☒ No									
5 TYPE OF CASING USED:									
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued ☒ Clamped	
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (Specify below)		Welded	
				7 Fiberglass		SDR-26		Threaded	
Blank casing Diameter 5 in. to 25 ft., Dia		in. to ft., Dia		in. to ft., Dia		in. to ft., Dia		in. to ft., Dia	
Casing height above land surface 12 in., weight 2.35 lbs. / ft.		lbs. / ft.		Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel		3 Stainless Steel		5 Fiberglass		7 PVC		10 Asbestos-cement	
2 Brass		4 Galvanized steel		6 Concrete tile		8 RMP (SR)		11 other (specify)	
						9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENING ARE:									
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes			
				7 Torch cut		10 Other (specify)			
SCREEN-PERFORATION INTERVALS: from 25 ft. to 50 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: from 24 ft. to 50 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens		14 Abandon water well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage		16 Other (specify below)	
Direction from well? East How many feet? 20									
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0	4	topsoil							
4	12	clay							
12	15	fine sand							
15	25	clay							
25	27	fine sand							
27	50	shale							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/08/00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 08/11/00 Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp									