LOC	ATION OF W	ATER WELL:	FRACTION	W	ater Well Reco	ord Form WWC-	KSA 82a-1212 Section Numbe	- 1		I		
الم	Sedgr			/4 NE	1/4	NW 1/4	3	0.5		Range Number		
Distance	Distance and direction frem nearest town or city street address of well if loc					IAM 1/4		т 27	S	R 2E EA	Ŋ	
3	/4 W.	of Santa	Fe Lake	Road o	on N.	side o	f 21gt	S+				
	ATER WELL		RPOINT, C		<u> </u>	DIGC C	1 4100	<u> </u>				
RR#	, ST. ADRESS		40 SW 70t			Board of Agriculture, Divivsion of Water Resource						
CITY, STATE, ZIP CODE: Augusta, Kansa									Application Number:			
	TE WELL'S	LOCATION WITH	DEPTH OF			107	ft. E	LEVATION:				
~~~	IN SECTIO	N N	Depth(s) grou			1	ft.	2	ft.		t.	
11	^		WELL'S STATI					SURFACE MEASURED		10/19/200	0	
Ì '	<b>NW</b>	NE	Est. Yield	test data:		water was	ft.	after	hours pum		gpm	
1Mile			Bore Hole Diame	gpm: ter 12		to 107	ft. ft.	after and	hours pum in.		gpm ft.	
\frac{1}{2} v	۷ <u> </u>	E	WELL WATER			5 Public wate		8 Air conditionir		ijection well	14.	
١.			1 Domestic	3 Feed		6 Oil field wa		9 Dewatering	•	ther (Specify below)		
11			2 Irrigation	4 Indu	ıstrial	7 Lawn and g	arden only	10 Monitoring we	:11			
· · · · · · · · · · · · · · · · · ·									X ; If yes, m	o/day/yr sample was		
5 TX	DE OF CA		submitted				v	Vater Well Disinfect		X No		
1 Ste		SING USED: 3 RMP (SR)			ought iron estos-Cem		Concrete tile	CASING J		lued X Clamped		
2 PVC 4 ABS					estos-Cem erglass	,	Other (Specify	y Delow)	-	Welded Threaded		
	 asing Diam		in. to 40		ergiass Dia		DR-26	A D:	_			
1	•	ve land surface 1		ft., in.,	welght	in. 235	to lbs. / ft.	ft., Dia Wall thickness or	in. gange No	to ft.		
			TION MATERIA	L:		7	PVC		Asbestos-ceme	. 2 1 7 nt		
1 Steel 3 Stainless Steel 5 Fiberglass						8	RMP (SR)	11	other (specify	)		
2 Brass 4 Galvanized steel 6 Concrete						rete tile 9 ABS			12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE:  1 Continous slot 3 Mill slot					5 Gauzed wrapped			8 Saw cut 11 None (open hole)			e)	
1		3 Mill sl			6 Wire wrapped			9 Drilled holes				
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATION INTERVALS: from 40 ft to 107 ft From 9 ft												
SCREE	M-PERFO	RATION INTERV		40		t. to 107	ft., Fro		ft. to		ft.	
GRAVEL PACK INTERVALS: from 24					ft. to ft. to 1		ft., Fr ft., Fr		ft. to		ſt.	
from					ft. to		ft., Fr		ft. to ft. to		ft. ft.	
6 GRO	OUT MAT	ERIAL: 1 Neat	cement	2 Cement g			itonite			hole plug		
Grout Intervals: From ft. to					ft. From ft		to ft. F		4		ft.	
What is the nearest source of possible contamination:  1 Septic tank 4 Lateral lines					<b>.</b>		10 Livestock pens		14 Abandon water well			
2 Davetin mics					Plt privy		11 Fuel storage 12 Fertilizer storage		15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit					Sewage lag Feedyard			mzer storage cticide storage				
	on from wel		age pit	91	reeuyaru			•	-49 000			
FROM			LITHOLOGIC LO	OG		FROM	TO	How many fo	GING INTER	VALS	—	
0	3	topsoil										
3	12	clay	_			ļ						
12 81	81 107	brown sh						72.				
<u>от</u>	10/	grey sha	те			<del>-</del>	1					
									71.4			
*******												
7 CO	NTRACTO	R'S OR LANDOWNER	DIS CEDTIDICATION	This water	well was	(1) construct	ed (2) recons	tructed, or (3) plu	aged under ~	v jurisdiction and		
was c	ompleted	on (mo/day/year)	) <u>10/1</u> 9	<u> </u>	***************************************	and this red	ord is true to	the best of my kn	owledge and	belief. Kansas Wat	er	
Well C	Contractor	's License No	236	This Wa	ater Well I	Record was c	ompleted on	(mo/day/yr)	10/20	/00		
Unde	r the busir	ness name of.Hಡ	arp Well	&P.ump	Serv	ice, Ir	ໄΩ by (si	gnature)		_		
1									Todd S	. յար		