1 LOCATION OF WATER WELL:		FRACTION	W	ater Well Reco	ra romwwc	Section Number	Township Number	Range Number	
Sedgwick		SE	1/4 NW	1/4	SE 1/4	8	т 27 s	R 2E FAW	
Distance and direction frem nearest town or city street address of well if located within city?								R ZE E/W	
9048 E. Crestwood Wichita, Kansas									
May an Alles Supering									
					00		Application Number	<u> </u>	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.									
•	Ņ D	, .			1	ft.	2 ft.	3 ft.	
	WE		IC WATER I				RFACE MEASURED ON mo/day/yr	11/28/2000	
NW	NE		p test data:		water was		after hours pum		
اوا	1 1	Yield	gpm:		water was	ft.	after hours pum		
w Wille	1 : 121	Hole Diame			to 80	ft.	and in.	to ft.	
	V WEI		TO BE USE		5 Public wat			njection well	
sw	·SE·	1 Domestic	3 Fee	aiot ustrial	6 Oil field w			Other (Specify below)	
		2 Irrigation			7 Lawn and		10 Monitoring well	(1)	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was									
Submitted Water Weit Distincture: 1 es X 100									
ightharpoonup				ought iron		8 Concrete tile		lued X Clamped	
1 Steel	3 RMP (SR)			estos-Cem		9 Other (Specify b		Velded	
2 PVC	4 ABS		7 F1b	erglass	5	SDR-26	1	'hreaded	
Blank casing Diame	-	to 30	ft.,		ir		ft., Dia in.	to ft.	
	e land surface 12		in.,	weight	2.35		Wall thickness or gauge No. 10 Asbestos-ceme	.214	
	OR PERFORATION	MATERIA	AL: 5 Fibe	raloes		7 PVC 8 RMP (SR)			
i	3 Stainless Steel			_			11 other (specify	•	
2 Brass	4 Galvanized steel		6 Conc	rete tile		9 ABS	12 None used (or		
1	FORATION OPENIN	G ARE:			uzed wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot	3 Mill slot			6 Wir	re wrapped		9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 30 ft. to 80 ft., From ft. to								ft.	
		from		f	ft. to	ft., Fron	n ft. to	ft.	
GRAVEL PACK INTERVALS: from 24			24	ft. to 80		ft., Fron	n ft. to	ft.	
		from			ft. to	ft., Fron		n	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								hole plug	
Grout Intervals: From 4 ft. to 24				ft. From		to	ft. From	ft. to ft.	
What is the nearest source of possible contamination:			_	5 Du .		10 Livesto		bandon water well	
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel st	131	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon				16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? West How many feet? 30 FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
FROM TO		IOLOGIC I	LOG		FROM	ТО	PLUGGING INTE	RVALS	
0 3	topsoil						1.54		
3 19	clay								
19 80	grey shale							200	
								William Control	
								4.400	
	·						1		
							1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
				477					
									
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)									
was completed	on (mo/day/year)	11/2	28/00		and this r	ecord is true to t	he best of my knowledge and	l belief. Kansas Water	
Well Contractor	's License No <u></u> 2.	3.6	This W	later Well	Record was	completed on (r	no/day/yr)12/0	T.\.\.\.\.	
Under the busin	ess name of Harp	wett"	&R.UMI	ser	ATCE.""	.யிடி by (sig	nature) てんん	S. Нагр	
							zoun ,	J. J will P	