

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>1/4</u> <u>NW</u> <u>1/4</u> <u>NE</u> <u>1/4</u>	<u>14</u>	T <u>27</u> S	R <u>2E</u> E/W
Distance and direction from nearest town or city street address of well if located within city? <u>1301 St. Andrews Wichita Kansas</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #:		Application Number:			
City, State, ZIP Code:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>80</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>60</u> ft. 2. <u>80</u> ft. 3. <u>10-23-00</u> ft.			
		WELL'S STATIC WATER LEVEL <u>60</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was <u>10</u> ft. after <u>80</u> hours pumping <u>10-23-00</u> gpm			
		Est. Yield <u>10</u> gpm: Well water was <u>80</u> ft. after <u>10</u> hours pumping <u>10-23-00</u> gpm			
		Bore Hole Diameter <u>10</u> in. to <u>80</u> ft. and <u>10</u> in. to <u>80</u> ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial ⑦ Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No <u>X</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>			
1 Steel		5 Wrought iron			
② PVC		6 Asbestos-Cement			
3 RMP (SR)		8 Concrete tile			
4 ABS		9 Other (specify below)			
7 Fiberglass		Welded <u>SDR 24</u>			
Blank casing diameter <u>5</u> in. to <u>60</u> ft., Dia <u>18</u> in. to <u>18</u> in., weight <u>18</u> lbs./ft. Wall thickness or gauge No. <u>SDR 24</u>		Threaded <u>SDR 24</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:		⑦ PVC			
1 Steel		10 Asbestos-cement			
3 Stainless steel		8 RMP (SR)			
5 Fiberglass		11 Other (specify)			
2 Brass		12 None used (open hole)			
4 Galvanized steel		6 Concrete tile			
9 ABS		11 None (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped			
1 Continuous slot		8 Saw cut			
③ Mill slot		11 None (open hole)			
2 Louvered shutter		6 Wire wrapped			
4 Key punched		9 Drilled holes			
7 Torch cut		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From <u>60</u> ft. to <u>80</u> ft., From <u>60</u> ft. to <u>80</u> ft.			
GRAVEL PACK INTERVALS:		From <u>15</u> ft. to <u>80</u> ft., From <u>15</u> ft. to <u>80</u> ft.			
6 GROUT MATERIAL:		③ Bentonite			
1 Neat cement		4 Other			
2 Cement grout		10 Livestock pens			
Grout Intervals: From <u>4</u> ft. to <u>15</u> ft., From <u>4</u> ft. to <u>15</u> ft.		11 Fuel storage			
What is the nearest source of possible contamination:		12 Fertilizer storage			
1 Septic tank		13 Insecticide storage			
4 Lateral lines		14 Abandoned water well			
7 Pit privy		15 Oil well/Gas well			
8 Sewage lagoon		16 Other (specify below)			
2 Sewer lines					
5 Cess pool					
3 Watertight sewer lines					
6 Seepage pit					
9 Feedyard					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	22	Clay			
22	35	Shale			
35	38	Lime			
38	54	Shale			
54	80	Cherty lime			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-23-00</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>171</u> This Water Well Record was completed on (mo/day/yr) <u>11-15-00</u> under the business name of <u>G+S Drilling Inc</u> by (signature) <u>[Signature]</u>					