


WATER WELL RECORD Form WW-5 KSA 82a-1212 ID No.						CM9166	
1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number		
County: Sedgwick		SE 1/4 SE 1/4 SE 1/4	18	T 27 S	R 2 E		
Distance and direction from nearest town or city street address of well if located within city? 7990 E Central							
2 WATER WELL OWNER:							
RR#, St. Address, Box # : City, State, ZIP Code :				Board of Agriculture, Division of Water Resources Application Number:			
Coastal Mart, Inc. Nine Greenway Plaza Houston TX 77046							
3 LOCATE WELL'S LOCATION WITH		4 DEPTH OF COMPLETED WELL: 15 ft. ELEVATION:					
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1. .ft. 2. .ft. 3. .ft.					
		WELL'S STATIC WATER LEVEL .ft. below land surface measured on mo/day/yr					
		Pump test data: Well water was .ft. after . hours pumping . gpm					
		Est. Yield . gpm: Well water was .ft. after . hours pumping . gpm					
		Bore Hole Diameter: 8.5 in. to 15 .ft., and . in. to .ft.					
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well MW-2					
Was a chemical/bacteriological sample submitted to Department? Yes. . No. X If yes, mo/day/yr sample was submitted							
Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED:							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. . Clamped. .							
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded .							
Blank casing diameter . 2 .in. to 5 .ft., Dia .in. to .ft., Dia .in. to .ft.							
Casing height above land surface . Flush . in., weight . 703 . lbs./ft. Wall thickness or gauge No. Sch 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement							
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)							
9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes							
7 Torch cut 10 Other (specify) .ft.							
SCREEN-PERFORATED INTERVALS: From . 5 .ft. to 15 .ft., From .ft. to .ft.							
GRAVEL PACK INTERVALS: From . 3 .ft. to 15 .ft., From .ft. to .ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .ft.							
Grout Intervals: From . 1.5 .ft. to 3 .ft., From .ft. to .ft., From .ft. to .ft.							
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)							
13 Insecticide storage							
Direction from well? SW How many feet? 75							
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS		
0	4.5	Clay					
4.5	7.5	Clayey sand					
7.5	15	Clay					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/30/00 and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's Licence No. 531 This Water Well Record was completed on (mo/day/yr) 11/4/01							
under the business name of Geotechnical Services, Inc. by (signature) [Signature]							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.							