

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction NW 1/4 NE 1/4 SE 1/4	Section Number 20	Township Number T 27 S	Range Number R 2 EW
Distance and direction from nearest town or city street address of well if located within city? 9333 EAST DOUGLAS WICHITA, KS MW# 64-S					
2 WATER WELL OWNER: RAYTHEON AIRCRAFT CO RR#, St. Address, Box #: 9709 EAST CENTRAL City, State, ZIP Code: WICHITA, KS 67207		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 1/4 in. to 30 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) ☒ PVC 2 ABS Blank casing diameter 2 in. to 20 ft., Dia 0 in. to ft., Dia in. to ft. Casing height above land surface in., weight 40 lbs./ft. Wall thickness or gauge No.		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ☒ 3 Mill slot 0.10 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30 ft. to 20 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 30 ft. to 18 ft., From ft. to ft.			
6 GROUT MATERIAL: 15 1 Neat cement - .03 Cement grout 18 ☒ Bentonite 15 4 Other Grout Intervals: From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well ☒ 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? EAST How many feet? 200					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	ASPHALT			
0.5	1	LIMESTONE GRAVEL & SILT			
1	3	DARK BRN SILTY CLAY			
3	7	YELLOW BRN SILTY CLAY			
7	11	SILTY OLIVE CLAY			
11	12	OLIVE CLAYEY SILT			
12	15	OLIVE SILTY CLAY			
15	16	OLIVE CLAYEY SILT			
16	18	YELLOW BRN SILTY CLAY			
18	25	LIGHT OLIVE BRN SILTY CLAY			
25	27	LIGHT OLIVE BRN CLAYEY SILT			
27	30	VERY DARK GREYISH BRN SILTY SHALE SATURATED			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-10-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 8-3-98 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)					