


1] LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>NW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	<u>12</u>	<u>T</u> <u>27</u> <u>S</u>	<u>R</u> <u>2</u> <u>EX</u>
Distance and direction from nearest town or city street address of well if located within city?					
<u>1730 Sagebrush Wichita, KS 67230</u>					
2] WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
<u>Kennedy</u>		<u>c/o McCollom Construction</u>			
<u>401 State St., Augusta, KS 67010</u>					
3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4] DEPTH OF COMPLETED WELL: <u>80</u> ft. ELEVATION:			
N 1 Mile W E S 		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>15</u> ft. below land surface measured on mo/day/yr <u>2/25/98</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: <u>9 1/2</u> in. to <u>80</u> ft., and in. to ft.			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued ☒ Clamped			
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
<u>2 PVC</u>		4 ABS	7 Fiberglass		Threaded
Blank casing diameter <u>5</u> in. to <u>40</u> ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SDR26</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		☒ PVC			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	☒ Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS: From <u>40</u> ft. to <u>80</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>80</u> ft., From ft. to ft.					
GROUT MATERIAL:		4 Other			
1 Neat cement		2 Cement grout	<u>3</u> Bentonite		
Grout Intervals: From <u>4</u> ft. to <u>20</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens			
1 Septic tank		4 Lateral lines	7 Pit privy	14 Abandoned water well	
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	
				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	24	Clay			
24	39	Clay & Shale			
39	44	Lime			
44	65	Shale			
65	80	Shale with Lime Streaks			
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>2/25/98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>171</u> This Water Well Record was completed on (mo/day/yr) <u>3/2/98</u> under the business name of <u>G & S Drilling, Inc.</u> by (signature) <u>[Signature]</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					