Line	TON OF U				Water \	Well Reco	ord Form	WWC-5	KSA 82a-1212						
LILOCA	TION OF W Sedgw:	ATER WELL:	FRACTIO		SW		NW		Section Number	'	Township Num	ber	Rai	nge Number 2E	
Distance and direction frem nearest town or city street address of well if lo			1/4 f well if loca		1	INW	1/4			_T 27	S	R	<u> </u>	E/W	
8306 Bridlewood Wichita, Kansas															
WA	TER WELL	OWNER: DWER	LKOTTE, 1						**************************************	Maria					
RR#,	ST. ADRESS		Bridlew								Board	of Agriculture, Di	ivivsion of W	ater Resourc	ce
CITY	, STATE, ZI	PCODE: Wich			Application Number							r:			
	TE WELL'S	LOCATION WITH ON BOX:			IPLETED		-	0 .		LEVATI		_	•		_
1 +		N	WELL'S STA		ater Encou		_	FT	ft. BELOW LAND S	2 SUBFACE	_	ft.	3 10-0	3-2001	ft. 1
			1	ump test			l water v		ft.	after	MEASURED	hours pum	-	J-2001	gpm
	NW	NE	Est. Yield	•	gpm:		l water v		ft.	after		hours pump			gpm
l ii w	/ X	E	Bore Hole Dia	ımeter	12	in.	to 9	0	ft.	and	d	in.	to		ft.
=			WELL WAT	ER TO B	3E USED A	AS:			r supply		conditioning	•	njection w		
11			tic	3 Feedlot				ter supply		vatering		ther (Spe	cify below	v)	
			2 Irrigatio		4 Industr				arden only		nitoring well				
Was a chemical/bacteriological sample submitted to Depa submitted									-			X; If yes, m		sample wa No	as
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped														-	
1 Stee	el	3 RMP (SR)			6 Asbesto	-			Other (Specify				elded/	Ciampea	
2 PV	<u>C</u>	4 ABS			7 Fibergl	ass		SI	DR-26			T	hreaded		
	asing Diar		in. to 30)	ft.,	Dia		in.	to	ft.,	Dia	in.	to	ft.	
_	-	ve land surface 1 EN OR PERFORA		in.,	v	veight 2	2.35	_	lbs. / ft.	Wall	thickness or	gauge No. Asbestos-ceme		.214	
1 Ste		3 Stainless Steel	ITON MATE		5 Fibergla	188		-	<u>PVC</u> RMP (SR)			other (specify)			
2 Bra		4 Galvanized ste	el		6 Concrete				ABS			None used (op	•		
SCREE	EN OR PE	RFORATION OPI			5 Gauzed wrapped					8 Saw cut			•	ie (open h	iole)
	nous slot	3 Mill sl		6 Wire wrapped					9 Drilled hole					,	
2 Louve	ered shutte	er 4 Key po	unched			7 Tore	ch cut			10	Other (spec	cify)			
SCREE	N-PERFO	RATION INTERV	VALS: fro	m 30		f	ft. to 90	ı	ft., Fro)m		ft. to			ft.
from						ft. to	ft., Fr				ft. to			ft.	
GRAVEL PACK INTERVALS: from 24						ft. to 90	· ·				ft. to			ft.	
6 GROUT MATERIAL: 1 Neat cement 2 C					ft. to			2 P	ft., From			ft. to	-11		ft.
_	DUI MAT ntervals:		ft. to	2 Ce	ement grout			3 Bentonite		4 U		tonite h	_	-	
What is the nearest source of possible contamination:					ft. From			ft. to 10 Live		ft. From estock pens		4 14 Al	ft. to bandon w		ft.
	ic tank	4 Later:			7 Pit privy					storage			Oil well/Gas well		
	er lines	5 Cess	pool		8 Sewage lagoon					ilizer sto	•		other (spec		v)
3 Wate	ertight sew	er lines 6 Seepa	age pit		9 Fee	dyard			13 Insec	cticide st	orage				
Direction FROM	n from we		TIOC	- I more			1	Н	low many fee						
0	3	topsoil	LITHOLOGIC	LUG			— FR	ROM	TO		PLUG	GING INTER	RVALS		
3	24	clay							1	WURLE II .					
24	26	sandy clay	У												
26	90	grey shale	8												
	ļ								ļ						
-													<u></u>		
									1						
									1						
									1						
ļ									ļ						
									 						
 -															
7 CO	NTRACTO	OR'S OR LANDOWNE	ER'S CERTIFICAT	ION: Thi	is water w	/ell wa	ıs (1 <u>) co</u> r	nstruc	ted, (2) recor	nstructe	ed, or (3) pl	ugged under	r my juri:	sdiction	and
Was c	ompleted	l on (mo/day/yea ntractor's License	r)	236	V.I		and	d this	record is true	e to the	best of my	knowledge	and belie	ef. Kans	as
		0-5-2001				IIIS WA	TIGE AAGIE	Reco	ru was comp)leted O	11		_	. .	
Unde	r the busi	ness name of	Harp Wel	11 & F	Pump Se	ervi	ce, I	nc	by	y (signa	iture)	Todd	'S. F.	tarp	
1														,	