I OCATION O	TOTAL STREET, SECRET W.	PRACTION .	Water Well Reco	rd Form WWC-5		T	
LOCATION OF WATER WELL:		FRACTION	3.779	C	Section Number	Township Number	Range Number
Sedgwick NE 1/4		1,7	274	SE 1/4	10	T 27 s	R 2E E/W
Distance and direction frem nearest town or city street address of well if located within city?  12610 Tallowwood Wichita, Kansas							
12610 Tallowwood Wichita, Kansas  WATER WELL OWNER: SIMPSON, Mike							
RR#, ST. ADR	DIM	PSON, MIKE LO Tallowwood				Board of Agriculture,	Divivsion of Water Resource
CITY, STATE		nita, Kansas	Application Number:				
	L'S LOCATION WITH	·	MPLETED WELL	75	ft. ELEV	VATION:	61.
AN "X" IN SEC		Depth(s) groundw		1	ft.	2 ft.	3 ft.
11		WELL'S STATIC W				FACE MEASURED ON mo/day/yr	10-03-2001
	- NE -	Pump test		water was	ft. a	ifter hours pur	mping gpm
1 1 "		Est. Yield		water was		after hours pur	
	E	Bore Hole Diameter	12 in.	to 75	ft.	and in.	
=		WELL WATER TO	BE USED AS:	5 Public water	•••		Injection well
-s		1 Domestic	3 Feedlot	6 Oil field wa		Dewatering 12 0	Other (Specify below)
		2 Irrigation	4 Industrial	7 Lawn and g		Monitoring well	
+ <u>-</u>	S	Was a chemical/bacte	eriological sample	submitted to D	•		mo/day/yr sample was
5 TYPE OF	CASING USED:	submitted				er Well Disinfected? Yes	
1 Steel	3 RMP (SR)		5 Wrought iron		Concrete tile		Glued X Clamped
			6 Asbestos-Ceme 7 Fiberglass		Other (Specify be	•	Welded Threaded
Plank assing D	4 ABS	in. to 25	•		DR-26		Threaded
Blank casing D	nameter > above land surface 1	10	ft., Dia	in. 2 3 5		ft., Dia in.	to ft.
		in., ATION MATERIAL:	weight 2		lbs. / ft. V PVC	Wall thickness or gauge No. 10 Asbestos-cem	. 214 nent
1 Steel	3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specif	
2 Brass	4 Galvanized ste		6 Concrete tile		ABS	12 None used (o	**
SCREEN OR	PERFORATION OP	ENING ARE:	5 Gau	zed wrapped		8 Saw cut	11 None (open hole)
1 Continous sle				e wrapped		9 Drilled holes	,
2 Louvered shu		ounched	7 Torc	••		10 Other (specify)	
SCREEN-PER	FORATION INTER			t. to 75	ft., From	ft. to	ft.
from				t. to	ft., From	rt. to ft. to	
GR.	GRAVEL PACK INTERVALS: from 2			ft. to 75 ft., I		ft. to	ft. ft.
from			,		ft., From	ft. to	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug							
Grout Intervals		ft. to	ft. From	ft. t	to	ft. From 4	ft. to 24 ft.
What is the nearest source of possible contamination:					10 Livestoc	k pens 14 A	Abandon water well
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel stor	15	Oil well/Gas well
2 Sewer lines 5 Cess pool			14			Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well? East How many feet? 12 FROM TO LITHOLOGIC LOG FROM TO PLUCGING INTERVALS							
FROM TO	topsoil	LITHOLOGIC LOG		FROM	TO	PLUGGING INTE	RVALS
3 7	clay						
7 75	brown sha	le		+	1		
					†		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)							
Water Well C	ontractor's Licens	e No236	This Wat	ter Well Reco	rd was complete	ed on	
(mo/day/yr) 10-5-2001 Under the business name of Harp Well & Pump Service, Inc. by (signature)  Jedd S. Harp							
Under the business name of Harp Well & Pump Service, Inc. by (signature)  Jedd S. Harp							