				Water Well Record	Form WWC-5	KSA 82a-1212			
1 LOCATION OF WATER WELL: FRACTION					Section Number	Township Number	Range Number		
Sedgwick NW 1/4			/4 SW 1/4 S	W 1/4	11	T 27 s	R 2E E/W		
Distance and direction frem nearest town or city street address of well if located within city?									
1538 Rocky Creek Rd. Wichita, Kansas									
WATER WELL OWNER: PHILLIPS, Dennis									
RR#, ST. ADRESS, BOX #: 1538 Rocky Creek Rd. Board of Agriculture, Divivsion of Water Resource									
CITY	, STATE, ZI	PCODE: Wich	ita, Kansa	8			Application Numbe	r:	
		LOCATION WITH	4 DEPTH OF	COMPLETED WELL	80	ft. ELE	VATION:		
AN "X	" IN SECTIO	N BOX:	Depth(s) grou	ndwater Encountered	1	ft.	2 ft.	3 ft.	
			WELL'S STATI	C WATER LEVEL 30	FT.	BELOW LAND SUR	RFACE MEASURED ON mo/day/yr	9-11-2001	
Pump test data: Well water was ft. after hours							after hours pum	ping gpm	
ي ا			Est. Yield	gpm: Well	water was	ft.	after hours pum	iping gpm	
Mile A	/ 	E	Bore Hole Diame	ter 12 in.	to 80	ft.	and in.	to ft.	
-			WELL WATER	TO BE USED AS:	5 Public wate	r supply 8	B Air conditioning 11 Is	njection well	
1 1	y sw-		1 Domestic		6 Oil field wa		Dewatering 12 O	Other (Specify below)	
11	r		2 Irrigation		7 Lawn and g		0 Monitoring well		
1 +		S		bacteriological sample s	ubmitted to D	epartment? Yes		no/day/yr sample was	
submitted Water Well Disinfected? Yes X No									
		ASING USED:		5 Wrought iron		Concrete tile		lued X Clamped	
1 Stee		3 RMP (SR)		6 Asbestos-Cemer	•	Other (Specify be	,	Velded	
2 PV		4 ABS		7 Fiberglass	SI	R-26	Т	`hreaded	
	asing Dian		in. to 40	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1			TION MATERIA	L: 5 Fiberglass		PVC	10 Asbestos-ceme		
Total (Specify)								•	
2 Brass 4 Galvanized steel 6 Concrete tile						ABS	12 None used (op		
					ed wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 40 ft. to 80 ft., From ft. to ft									
			from		to	ft., From	ft. to	ft.	
1					to 80	ft., From		ft.	
from ft. to ft., From ft. to								ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
What is the mannet source of south la south distributions							ft. to 24 ft.		
1 Septic tank 4 Lateral lines 7 Pit pi						10 Livestock pens 14 Abandon water well			
1				8 Sewage lago	11 Fuel storage zoon 12 Fertilizer storage		13 0	Oil well/Gas well	
2 300 p.c.					OII	n 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage			
o seepage pit 9 reedyard									
FROM			LITHOLOGIC L	OG	FROM	ТО	How many feet? 110 PLUGGING INTE	DVALS	
0	3	topsoil			T TROM		TLUGGING INTE	NYALS	
3	19	clay							
19	80	grey shale	e						
	l					<u> </u>			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)9-11-2001 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No									
(mo/d	(mo/day/yr)9-12-2001 Under the business name of Harp Well & Pump Service, Inc								
Under the business name of Harp Well & Pump Service, Inc by (signature) Todd S. Harp									