LOCATION	OF WATER WELL.	FRACTION	Water Well Reco	ord Form WWC-		T	T
LOCATION OF WATER WELL: Sedgwick		1	SE 1/4	CM	Section Number	Township Number	Range Number
		1,1	1,7	SW 1/4	11	T 27 S	R 2E E/W
Distance and direction frem nearest town or city street address of well if located within city?  1451 Glenwood Ct. Wichita, Kansas							
WATER WELL OWNER: DENZIN, Greg  RR#, ST. ADRESS, BOX #: 1451 Glenwood Ct.  Board of Agriculture, Divivsion of Water Resource							
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:							
			APLETED WELL	. 75	ft. ELE	VATION:	1.
	SECTION BOX:	Depth(s) groundwa		1	ft.	2 ft.	3 ft.
		WELL'S STATIC W		5 гт	. BELOW LAND SUR	FACE MEASURED ON mo/day/yr	8-7-2002
	-NW	Pump test	t data: Well	water was	ft. a	ıfter hours pum	iping gpm
		Est. Yield	gpm: Well	water was		after hours pum	
l ii w ⊢	- E	Bore Hole Diameter	12 in.	to 75	ft.	and in.	to ft.
= "		WELL WATER TO I	BE USED AS:	5 Public water	er supply 8	3 Air conditioning 11 In	njection well
1 i	-sw	1 Domestic	3 Feedlot	6 Oil field wa	ater supply 9	Dewatering 12 O	Other (Specify below)
		2 Irrigation	4 Industrial	7 Lawn and		Monitoring well	
+ -		Was a chemical/bacte	eriological sample	submitted to l	-	· · ·	no/day/yr sample was
submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded							
Plank seeing	4 ABS	in. to 40	7 Fiberglass		DR-26		`hreaded
	g Diameter 5 ht above land surface 12	•	ft., Dia	in. 25		ft., Dia in.	to ft. .214
	CREEN OR PERFORAT		weight 2		lbs. / ft. PVC	Wall thickness or gauge No. 10 Asbestos-ceme	
1 Steel	3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify	<b>'</b> )
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
SCREEN O	R PERFORATION OPE	NING ARE:	5 Gau	uzed wrapped		8 Saw cut	11 None (open hole)
1 Continous	s slot 3 Mill slo	ot		e wrapped		9 Drilled holes	, ,
2 Louvered	shutter 4 Key pu	nched	7 Toro	ch cut		10 Other (specify)	
SCREEN-PERFORATION INTERVALS: from 40 ft. to 75 ft., From ft. to ft.							
		from		t. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS: from 24				ft. to 75	ft., From	ft. to	ft.
from			f	t. to	ft., From ft. to		.ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug							
Grout Intervals: From 4 ft. to 24 ft. From					to ft. From ft. to ft.		
What is the nearest source of possible contamination  1 Septic tank  4 Lateral lines			10 Livestock pens 7 Pit privy 11 Fuel storage			bandon water well	
						13 (	Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard					12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage		
-		ITHOLOGIC LOG		FROM	How many feet? 20 FROM TO PLUGGING INTERVALS		
0 4	topsoil						
4 70							
70 75	limestone						
		Pr					
					+		
					+ +		
		***************************************			-		
	***************************************						
						1000000	
7 CONTRACTOR'S ON LANDOWNERS CERTIFICATION. This water well was (1) constructed (2) reconstructed or (2) plugged under my jurisdiction and							
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
Water Well Contractor's License No							
1							
Under the business name of Harp Well & Pump Service, Inc. by (signature)  Under the business name of Harp Well & Pump Service, Inc. by (signature)							