				Water Well Record	Form WWC-5	KSA 82a-1212			
LOCATION OF WATER WELL: Sedgwick			FRACTION	<b>NTP</b> (1)	.,	Section Number	Township Number	Range Number	
			NE 1/4 SI	1/4	7.7	T 27 S	R ZE E/W		
Distance and direction frem nearest town or city street address of well if located within city?									
1704 N. Rocky Glen Wichita, Kansas  Water well owner: Darry Rill									
WATER WELL OWNER: DAKEN, Bill  RR#, ST. ADRESS, BOX #: 1704 N. ROCKY Glen  Board of Agriculture, Division of Water Resource									
	, STATE, ZIP		ita, Kansas	ren	Application Nu				
		OCATION WITH	r r	OMPLETED WELL	80	ft. ELE	VATION:	Det.	
	" IN SECTIO		<u></u>	lwater Encountered	1	n. ELE ft.	2 ft.	3 ft.	
1 +		N	,.	WATER LEVEL 30			RFACE MEASURED ON mo/day/yr	5-15-2002	
					ater was		after hours pu		
1 '		NE	Est. Yield		vater was		after hours pu		
w Kile			Bore Hole Diamete	01	to 80	ft.	and in		
∑ w		X	WELL WATER TO		Public wate			Injection well	
Ι.		_     	1 Domestic	3 Feedlot 6	Oil field wa	ter supply	9 Dewatering 12	Other (Specify below)	
	-sw-	- ] <b>3</b> <u>E</u> ]	2 Irrigation	4 Industrial 7	Lawn and g	arden only 1	0 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes							No X; If yes,	mo/day/yr sample was	
S submitted Water Well Di								X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
1 Stee	l	3 RMP (SR)		6 Asbestos-Cemen	t 9	Other (Specify b	elow)	Welded	
2 PVC	<u> </u>	4 ABS		7 Fiberglass	SI	DR-26		Threaded	
Blank ca	asing Dian	ieter 5	in. to 40	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214  TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1			ATION MATERIAL	: 5 Fiberglass		PVC PMP (SP)			
Statistics Steel								•,	
2 Brass 4 Galvanized steel 6 Concrete tile						ADS	8 Saw cut	• • •	
SCREEN OR PERFORATION OPENING ARE:					5 Gauzed wrapped				
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
			ounched	7 Torch			10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 40 ft. to 80 ft., From ft. to									
from GRAVEL PACK INTERVALS: from				ft. to		ft., From			
					to 80	ft., From		-	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Court Intervals: Firm 4								ft. to ft.	
What is the nearest source of possible co				it. From			ft. From ck pens 14	Abandon water well	
1 Septic tank 4 Lateral			ral lines	7 Pit privy		11 Fuel ste	orage 15	6 Oil well/Gas well	
2 Sewe	r lines	5 Cess	s pool	8 Sewage lagoon			zer storage 16	Other (specify below)	
3 Wate	rtight sew		age pit	9 Feedyard		13 Insecticide storage			
Direction from well? West How many feet? 30									
							PLUGGING INT	ERVALS	
0	4	topsoil							
4	15	clay						1 4. 1 1 1 1 1	
15	80	shale			<b></b>				
-						1			
					1	<del> </del>			
					1	<u> </u>			
				· · · · · · · · · · · · · · · · · · ·	<del> </del>		<del> </del>		
	1					1			
								**************************************	
					İ				
			·						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Water	Well Cor	tractor's Licens	se No	6 This Wate	er Well Rec	ord was comple	eted on	•	
(mo/d	(mo/day/yr) 5-17-2002								
Under the business name of Harp Well & Pump Service, Inc. by (signature)  Jodd S. Harp									