				Water Well	Record Form WWC	-5 KSA 82a-1212		
1 LOCA		VATER WELL:	FRACTION			Section Number	Township Number	Range Number
Distance	Sedgw		NW 1/4		SW 1/4	11		R 2E E/W
1		cky Creek C	ity street address of well it	•	Vanasa			
1501 Rocky Creek Ct. Wichita, Kansas WATER WELL OWNER: HERBERT, Mike								
RR#, ST. ADRESS, BOX #: 1501 Rocky Creek Ct. Board of Agriculture, Divivsion of Water Resource								
CITY	Y, STATE, ZI	PCODE: Wich	ita, Kansas	ı			Application Numbe	er:
	TE WELL'S	LOCATION WITH	4 DEPTH OF C	OMPLETED WE	ELL 80	ft. EL	EVATION:	
AN "X	I'' IN SECTIO	ON BOX:	,	dwater Encounter		ft.	2 ft.	3 ft.
			WELL'S STATIC				URFACE MEASURED ON mo/day/yr	4-17-2002
'		NE	Est. Yield		Vell water was	ft.	after hours pum	
Mile M			Bore Hole Diamete	61	Vell water was 1. to 80	ft. ft.	after hours pum and in.	iping gpm to ft.
= M	'	E	WELL WATER T		5 Public wat			njection well
١.	-cn/-		1 Domestic	3 Feedlot		vater supply	•	Other (Specify below)
	Sw-		2 Irrigation	4 Industrial	7 Lawn and	garden only	10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was								
	TDE OF 6	S	submitted			Wa	ater Well Disinfected? Yes	
5 TY		ASING USED:		5 Wrought i		8 Concrete tile		Glued X Clamped
l		3 RMP (SR) 4 ABS		6 Asbestos-C 7 Fiberglass		9 Other (Specify I	•	Velded Threaded
2 PVC	_		in. to 40	ŭ	-	SDR-26		
Blank casing Diameter 5 in. to 40 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214								
			TION MATERIAL	., weig	•	7. <u>PVC</u>	10 Asbestos-ceme	
1 Steel 3 Stainless Steel 5 Fiberglass						8 RMP (SR) 11 other (specify)		
2 Brass 4 Galvanized steel 6 Concrete tile					e	9 ABS	12 None used (or	en hole)
	SCREEN OR PERFORATION OPENING ARE: 5 Gauze					• •		
1 Continous slot 3 Mill slot 6 Wire wrapped							9 Drilled holes	
	ered shutte	J P			Forch cut		10 Other (specify)	
SCREE	N-PERFU	DRATION INTERV		; O	ft. to 80	ft., Fron		ft.
	CDAV	TO DACK INTED	from	3.4	ft. to	ft., Fron		ft.
_					ft. to 80 ft. to	ft., Froi ft., Froi		ft. ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout I	ntervals:	From 4	ft. to 24	ft. From	ft.	to	ft. From	ft. to ft.
What is the nearest source of possible contamination:						10 Livestock pens 14 Abandon water well		
1 Septic tank 4 Lateral lines 7 Pit pri					•	11 Fuel storage		Oil well/Gas well
	er lines	5 Cess	•	8 Sewage	9	12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent		
l	ertight sew	•	age pit	9 Feedya	ırd	IJ Inset.	None	Apparent
Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								DVAIS
0	4	topsoil						WALS.
4	15	clay	-					
15	75	shale					and the state of t	
75	80	limestone						
							BANKAR PROPERTY OF THE PROPERT	
			TO A PROPERTY AND A STATE OF THE STATE OF TH					
		*				- - - - - - - - - - 		
		1 100 11						
							The state of the s	
							- 144 4 14 14 14 14 14 14 14 14 14 14 14	
					***************************************			· ·
	<u> </u>							
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
4 40 0000								
(mo/day/yr)4-19-2002 Under the business name of Harp Well & Pump Service, Inc								