				Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCATION OF WATER WELL:			FRACTION			Section Number	Township Number	Range Number
Sedgwick			NE 1/4	NE 1/4 SV	W 1/4	11	_T 27 s	R 2E E/W
i			city street address of well if loo	-				
13508 Tallowood Wichita, Kansas								
WATER WELL OWNER: HERNDON, Brad								
	, ST. ADRESS		8 Tallowood				_	Divivsion of Water Resource
	Y, STATE, ZI		nita, Kansas				Application Number	er:
	ATE WELL'S (" IN SECTIO	LOCATION WITH ON BOX:		MPLETED WELL	80		VATION:	
t		N I	Depth(s) groundw		1 FT	ft.	2 ft. RFACE MEASURED ON mo/day/yr	3 ft. 1-30-2003
WELL'S STATIC WATER LEVEL 30 Pump test data: Well water y							• •	
'	NW-	— NE	Est. Yield	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	vater was vater was		after hours pun after hours pun	
1 Mile			Bore Hole Diameter	10	to 80	it. ft.	atter nours put and in.	nping gpm to ft.
\(\frac{1}{2}\) \(\frac{1}{2}\)	'	7	WELL WATER TO		Public water			Injection well
1	L		1 Domestic		Oil field was	***		Other (Specify below)
	-sw-	SAL	2 Irrigation		Lawn and g		0 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X: If yes,							No X; If yes, n	no/day/yr sample was
		S	submitted			-	er Well Disinfected? Yes	• • •
		ASING USED:		5 Wrought iron	8	Concrete tile	CASING JOINTS: G	Glued X Clamped
1 Stee		3 RMP (SR)		6 Asbestos-Cemen	t 9	Other (Specify be		Velded
2 PV		4 ABS		7 Fiberglass	SD	R-26	Т	Threaded
	asing Dian		in. to 40	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Ste		EN OR PERFORA 3 Stainless Steel		5 Fiberglass	-	<u>PVC</u> RMP (SR)	10 Asbestos-cem	
2 Brass 4 Galvanized steel 6 Concrete tile						9 ABS 11 other (specify) 12 None used (open hole)		
						Abs	8 Saw cut	• ′
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wr 1 Continuous slot 3 Mill slot 6 Wire wrapp						8 Saw cut 11 None (open hole) 9 Drilled holes		
	ered shutte	-			• •		10 Other (specify)	
				7 Torch		2 P		
1 10 10						ft., From	ft. to	ft.
from GRAVEL PACK INTERVALS: from 24					ft. to ft., Fron ft. to 80 ft., Fron			ft.
	0.01	EL TACITA	from		ft. to ft., From			ft.
6 GR(DUT MAT	ERIAL: 1 Neat		Cement grout	3 Ben		4 Other bentonite h	
Grout Intervals: From 4 & 6 to 24							ft. to ft.	
		st source of possibl			10 Livestock pens			Abandon water well
1 Septic tank 4 Lateral lines			al lines	7 Pit privy		11 Fuel sto	- 13(Oil well/Gas well
2 Sewer lines 5 Cess pool					8		er storage 16 (Other (specify below)
	ertight sew	•	oage pit	9 Feedyard		13 Insectio	eide storage	
Direction from well? North How many feet? 15								
FROM 0	TO 4	topsoil	LITHOLOGIC LOG		FROM	TO -	PLUGGING INTE	RVALS
4	15	clay						
15	80	shale		W. C. Carriera W. C. Carriera C. C. Carriera C. Carrie			1 (1879)	
		-				·		
			Wilderson and American Control of the Control of th					
							7,5 8,7 1	
	\vdash							
							1.000	
							9.44	
						ļ		
1								
CONTRACTOR'S or Landowner's Certification: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
(mo/day/yr)1-31-2003								
Under the business name of Harp Well & Pump Service, Inc. by (signature) Jodd S. Harp								
Under the business name of Harp Well & Pump Service, Inc by (signature) Todd S. Harp								