LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	Section Number	Township Number	Range Number
Sedgwick	NE 1/4	SW 1/4 SV	N 1/4	9	T 27 S	2E
Distance and direction frem nearest town or city street address of well if located within city?						
900' E. & 900' N. of Intersection of 13th N. & Webb Rd. Wichita, KS.						
		OH OF THE	A. & HEL	D Ru.	Wichita, RD.	
5111	S, John	lBuilding I	300		Board of Agriculture, D	Divivsion of Water Resource
				67206 Application Number:		
		Manager VIII	63			
DOCATE WEELS LOCATION WITH						
Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 2-11-2003						
	Pump tes					
NW NE	•		ater was	ft.	after hours pum	
Les Les	t. Yield	81	vater was	ft.	after hours pum	
	re Hole Diameter	3 5	to Dublic mater	ft.	and in.	to ft.
	ELL WATER		Public water			njection well Other (Specify below)
	1 Domestic		Oil field wa			ther (specify below)
1 🗥	2 Irrigation	•	Lawn and g		10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was						
submitted Water wen Distincted. Tes 22 / NO						
5 TYPE OF CASING USED:		. 5 Wrought Iron		Concrete tile		dued Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Cemen	τ 9	Other (Specify		Velded Threaded
2 PVC 4 ABS		7 Fiberglass				
Blank casing Diameter 6 in	. to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height and surface 36 TYPE OF SCREEN OR PERFORATION	in.,	weight	-	lbs. / ft. PVC	Wall thickness or gauge No. 10 Asbestos-ceme	ent
	JN MATERIAL:	5 Fiberglass		RMP (SR)	11 other (specify	
1 Steel 3 Stainless Steel		6 Concrete tile		ABS	, , ,	,
2 Brass 4 Galvanized steel			-	ABS	12 None used (op 8 Saw cut	` '
1			ed wrapped			11 None (open hole)
1 Continous slot 3 Mill slot 6 Wi			wrapped		9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torc			cut		10 Other (specify) N/	'A
SCREEN-PERFORATION INTERVA	LS: from	ft.	to	ft., Fro	m ft. to	ft.
1	from	ft.	to	ft., Fro	m ft. to	ft.
GRAVEL PACK INTERVALS: from		ft. to ft., Fro		om ft. to	ft.	
	from	ft.		ft., Fro		ft
6 GROUT MATERIAL: 1 Neat cen	ient 2 C	Cement grout	3 Ben	itonite	4 Other bentonite h	nole plug
Grout Intervals: From ft. to		ft. From ft. to		ft. From 3 ft. to 63 ft.		
What is the nearest source of possible contamination:				stock pens 14 Abandon water well		
1 Septic tank 4 Lateral lines				storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess pool		12 I		tilizer storage 16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent					Apparent	
Direction from well? How many feet?						
FROM TO LIT	HOLOGIC LOG		FROM	ТО	PLUGGING INTE surface clay & sil	RVALS
			0	3	bentonite hole plu	
			3	63	benconite noie più	<u>.g</u>
				 		
				-		
					The state of the s	
			 			
						
				 		
				-	4441	
				- l-		4-1-1-1
l				-		
					The state of the s	
			J	<u></u>		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and						
was completed on (mo/day/year).	2-11-20	03	and this	record is true	to the best of my knowledge	and belief. Kansas
Water Well Contractor's License N	o236	This Wate	r Well Reco	ord was comp	leted on	
(mo/day/yr) 2-14-2003 To July S Hone Woll & Pump Service Inc.						
Under the business name of Harp Well & Pump Service, Inc by (signature) Tedd S. Harp						