	WATER WEI	LL RECORD	Form	WWC-5 K	SA 82a-121	2		
1 LOCATION OF WATER WELL:	FRACTION	NE	N X Y	SECTION NUMBER			RANGE NUM	
Sedgwick Distance and direction from nearest town or city s	NE 1/4		SW 1/4	11	т 27	S	R 2E	E/W
,	ichita, Kansas	-						
2 WATER WELL OWNER: GOMEZ Board of Agriculture, Division of Water Resource								
RR#,ST. ADDRESS,BOX #: 1726 Glenwood								
	ita, Kansas		82	ZIP CODE:	ELEVATION:	Application Num	iber:	
WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLE		02	ft. ft.	ELEVATION.	ft.		ft.
 	oth of groundwater E	4	5 FT F		JRFACE MEASU		lay/yr: 7/26/0	
NWNE			ell water was		ft. after		of pumping @	gpm
1 1 1 1 1 1 1	Est. Yield:	01	ell water was	•	ft. after	hours	of pumping @	gpm
~ X	ore Hole Diameter	12 in.		to 82 ft.	and	in.	to	ft.
	ELL WATER TO BE Domestic 3. Fe	USED AS: eedlot 5. Pub	lic water su	oply 7. Lawn a	and garden only	9. Dewateri:	ng 11. Injecti 12. Other (Spe	
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
Was a chemical/bacteriological sample submitted to Department? Was a chemical/bacteriological sample submitted to Department? Was Water Well Disinfected? YES NO YES NO YES NO								
5 TYPE OF CASING USED:		7.5%		9. Other (Specify		NG JOINTS: (\sim	hreaded
1. Steel 3. RPM (SR) Welded Clamped								
2. PVC 4. ABS	6. Asbestos-C	•	crete tile					
1 -	in. to 42			in. to	,		in. to	ft.
Casing height above land surface:	12 in.,	Weigh	it: 2.35	lbs. / ft.	Wall this	ckness or gaug	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)								
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1. Continuous slot 3. Mill slo	1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)							
2. Louvered shutter 4. Key pu	ınched 6. Wi	re wrapped	<	8. Saw cut	10. Othe	r (specify)		
SCREEN - PERFORATION INTERVAL	From	42 ft.	to 8	32 ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24 ft.	to {	32 ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug								
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to What is the nearest source of possible contamination:						ft.		
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage						ide storage	15. Oil well/Ga	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? East How many feet? 80								
Direction from well? East From To	LITHOLOGIC	LOG	Fr	om To	How ma		GIC LOG	
0 5 fill								
5 65 shale								
65 82 limestone								
Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and								
was completed on (mo/day/year) 7-26-2003 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7-28-2003								
under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Jarp								