			WATER \	NELL RE	CORD	Form \	VWC-5	KSA 82a-13	212		
1 LOCATION	ON OF WATE	R WELL:	FRACTION			[5	SECTION NUM	BER TOWNS	HIP NUMBER	RANGE	NUMBER
├ Sedg	wick		NW 1/	4 NW	1/4 S	W 1/4	11	T	27 s	R 2	E E/W
Distance an	d direction fro	m nearest town or city	street address of v	vell if located w	ithin city?	L					
1611	Rocky C	Creek Ct.	Wichita,	Kansas							
2 WAT	ER WELL (OWNER: PAN	KARTZ, M	ike							
RR#,ST	ADDRESS	,BOX #: 1611	Rocky Cre	ek Ct.					Board of Ag	riculture, Division of	Water Resource
	CITY,	STATE: Wicl	hita, Kansas				ZIP CODE:		Application Nu	mber:	
3 LOCAT	TE WELL'S LO	CATION 4	DEPTH OF COM	IPLETED W	ELL:	75	ft.	ELEVATION	:		
HIM MITH	AN "X" IN SEC	CTION BOX:	pth of groundwa				ft.		ft.		ft.
11 -	N 1							011054054454		0/1	
		1 1	ELL'S STATIC V				LOW LAND	SURFACE MEAS		,,	7/03
	-NM	NE		Pump test da		water was		ft. after		s of pumping @	gpr
w Mile	1		Est. Yield:	gpm ter 12		l water was	75	ft. after		s of pumping @	gpm
<u> </u>		' ! !	Bore Hole Diame			to	75	ft. and	in.	to	ft.
l`.	- sw		ELL WATER TO L Domestic	3. Feedlot		water suni	ly C7. Law	n and garden or	9. Dewater	y	ection well
	1	1 1		4. Industrial				conditioning	10. Monitori		Specify below
'	S		Was a chemical/bac			-		NO		what mo/day/yr	was sample
			ıbmitted		•			s Water Well Dis	infected?	YES	NO
5 TY	PE OF CAS	ING USED:	5. Wroug	ht Iron	7. Fibergl	255 9	. Other (Spe	cify below) CA	ASING JOINTS:	Glued	Threaded
	1. Steel	3. RPM (SF	R) 5. Wildeg	in non	_		DR-26	, ,		Welded	Clamped
	2. PVC	> 4. ABS	6. Asbest	tos-Cement	8. Concre	ete tile	DK-20				
Blank cas	sing diamete	er 5	in. to	40 ft.,	Dia.	in	. to	ft.,	Dia.	in. to	ft.
Casing h	neight above	land surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wall	thickness or gau	ge No21	1
I -	-	OR PERFORATION	*****		woight.	2.00	103.711.	vva.	mickiness of gau	ge 11021	4
1. Stee		Stainless Steel	5. Fiberglas	s C	7. PVC	, ,	. ABS	11. (Other (specify)		
2. Bra	ss 4	. Galvanized	6. Concrete		8. RMP (S	R) 1). Asbestos-(None used (open	hole)	
SCREEN	OD DEDEC	RATION OPENING	OC ADE.		,-	,			(,	
	inuous slot			. Gauzed wr	annad	7	Torob out	0 D-	illed holes	11 None (onen hole)
					• •		Torch cut			i i. None (open hole)
2. Louv	ered shutte	r 4. Key pı	unched 6	. Wire wrap	ped	. 8.	Saw cut	10. Ot	her (specify)		
SCREEN	- PERFORA	TION INTERVAL	From	40	ft.	to 75	ft.,	From	ft.	to	ft.
			From		ft.	to	ft.,	From	ft.	to	ft.
6	RAVEL PA	CK INTERVALS:	From	24	ft.	to 75		From	ft.	to	ft.
			From		ft.	to	,	From			
a L coo	UT MATERI	AL C.	FIOIII			10	ft.,	From	ft.	to	ft.
	UT MATERI	i. Neat			ent Grout		3. Benton	ite	Other bent	tonite hole p	lug
1	Intervals:	From 4	ft. to	24	ft., Fro	m	ft. to	o ft.,	From	ft. to	ft.
1. Septi		ource of possible co 4. Lateral		7. Pit privy		10. Lives	tock pens	13. inse d	ticide storage	15. Oil well	Gas well
1				8. Sewage I	agoon	11. Fuel	storane		_		pecify below)
2. Sewe		5. Cess P		•	_		_	14. Aban	don water well		, ,
	rtight sewe	r line 6. Seepa South	ge pit	9. Feed yar	1	12. Fertii	izer storage				
	from well?		LITHOLOG	10.1.00			. T.	How r	nany feet? 20	2010 1 00	
From	To		<u>LITHOLOG</u>	IC LOG		Fror	n To		LITHOLC	OGIC LOG	
1	15	topsoil clav					_		-		
<u>4</u> 15	75	shale									
13	-/3	Silale					-	_			*****

<u> </u>			 								
7 Conf	tractor's or L	andowner's Certific	cation: This wate	er well was 1	construc	ted 2.	reconstruc	ted or 3.	plugged	under my jurisdic	ction and
		(mo/day/year)	9/17/2003	•				ny knowledge and	l belief		
İ								•		/2002	
Kansas	vvater Well	Contractor's Licens	se No.	236	ı nıs wate	r well record	was complet	ted on (mo/day/ye	ear) 9/22	/2003	
		some of II	337all 0. D	n Courie	Ina	by	(signature)	_	1110	11	
under th	ne business	name of Harp `	wen & run	ip Service	: Inc.	٠,	(0.3010.0)		lo d d S.	LL	