Form WWC-5 WATER WELL RECORD KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NWSedgwick NE SW 11 27 **2E** 1/4 Т E/W 1/4 1/4 S Distance and direction from nearest town or city street address of well if located within city? 13208 Tallowood Ct. Wichita, Kansas **KLUN** WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 13208 Tallowood Ct. Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 85 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION ft. WITH AN "X" IN SECTION BOX: ft Depth of groundwater Encountered: ft. 45 WELL'S STATIC WATER LEVEL 8/27/03 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm -WW NE Est. Yield: hours of pumping @ gpm Well water was ft. after Φ gpm ≌ 12 to 85 Bore Hole Diameter in. and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 1. Lawn and garden only SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 8. Air conditioning 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample (NO Was a chemical/bacteriological sample submitted to Department? Was Water Well Disinfected? (YES) submitted 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1 Steel Welded Clamped SDR-26 8. Concrete tile 6 Ashestos-Cement 4. ABS 2. PVC 5 Blank casing diameter in. 45 ft., Dia. Dia. ft. in. Casing height above land surface: 2.35 in.. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9 ABS 3. Stainless Steel 1. Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 8. Saw cut 2. Louvered shutter 10. Other (specify) 4. Key punched 6. Wire wrapped SCREEN - PERFORATION INTERVAL 45 ft. 85 From to ft., From ft. to ft From to ft., From ft. GRAVEL PACK INTERVALS: 24 ft. to 85 From ft., From ft. From ft. to ft.. From ft ft. **GROUT MATERIALS:** 6 Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From ft., From ft ft.. From ft. to What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit How many feet? 95 North Direction from well? From LITHOLOGIC LOG LITHOLOGIC LOG Τо From Тο topsoil clav brown shale 45 grev shale under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. 8/27/2003 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. 8/29/2003 236 This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. by (signature) under the business name of Harp Well & Pump Service Inc. Jodd S. Harp