WATER WELL RECORD	Form W	WC-5 K	SA 82a-	1212		
1 LOCATION OF WATER WELL: FRACTION	SE	CTION NUMBE				E NUMBER
Sedgwick NW 1/4 NE 1/4 SV	V 1/4	11	Т	27 S	R	2E E/W
Distance and direction from nearest town or city street address of well if located within city? 1722 Glenwood Wichita. Kansas						
1722 Glenwood Wichita, Kansas 2 WATER WELL OWNER: GRACY		***************************************			**	
RR#,ST. ADDRESS,BOX #: 1722 Glenwood				Board of A	griculture, Division	of Water Resource
CITY, STATE: Wichita, Kansas		ZIP CODE:		Application N	umber:	
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL:	83 ft		ELEVATIO	N:		
WITH AN "X" IN SECTION BOX: N Depth of groundwater Encountered:		ft.		ft.		ft.
WELL'S STATIC WATER LEVEL 43	FT. BEL	OW LAND SU	JRFACE ME	ASURED ON mo	o/day/yr: 9 ,	/10/03
1,1,1	water was		ft. after	hou	rs of pumping @	gpr
	water was	02	ft. after		irs of pumping @	
Bore Hole Diameter 12 in. WELL WATER TO BE USED AS:	to	83 ft.	and	in.	to	ft. njection well
	water supply	7. Lawn a	and garden o	9. Dewate	9	(Specify below
	l water supp	•	ditioning	10. Monito	ring well	
S Was a chemical/bacteriological sample submitted submitted	to Department?		NO Vater Well Di	,	, what mo/day/y	yr was sample NO
5 TYPE OF CASING LISED:	0	Other (Specify		CASING JOINTS:	=	Threaded
1. Steel 3. RPM (SR)	oo Ct	Other (Specify DR-26	(Delow)	ASING JOINTS.	Welded	Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concret	e tile 31	JK-20				,
Blank casing diameter 5 in. to 63 ft., Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surface: 12 in., Weight:	2.35	lbs. / ft.	Wa	ll thickness or ga	uge No2	14
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	•	ADC	41	Other (enesity)		
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SF		ABS Asbestos-Cer		Other (specify) None used (ope	n hole)	
SCREEN OR PERFORATION OPENINGS ARE:	., 10.	Aspestos-Cei	110111	Hone asca (ope	1111010)	
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7 T	orch cut	9. 0	rilled holes	11. None	e (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped		aw cut		Other (specify)	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	(
, p				other (specify)		
SCREEN - PERFORATION INTERVAL From 63 ft.	to 83	ft.,	From	ft.	to	ft.
From ft. GRAVEL PACK INTERVALS: From 24 ft.	to 83	ft.,	From	ft.	to	ft.
110111		ft.,	From	ft.	to	ft.
From ft. 6 GROUT MATERIALS: 1 Next coment 3 Coment Group	to	ft.,	From	ft.	to	ft.
1. Weat cement 2. Cement Group		3. Bentonite			tonite hole j	
Grout Intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:	•		ft.,	From		to ft.
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livesto	ck pens	13. Ins e	ecticide storage		II/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon	11. Fuel st	orage	14. Ab a	ındon water wel	l 16. Other	(specify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard	12. Fertiliz	er storage		10		
Direction from well? East	From	То	How	many feet? 12	OGIC LOG	
0 3 topsoil	1 10111	10		LITTIOL	OGIC LOG	
3 35 brown shale						
35 75 grey shale						
75 83 limestone	-	+				
	+	4				
7 Contractor's or Landowner's Certification: This water well was 1. construct		nconstructs d	05 3	nlugged	under my juriso	diction and
0/10/2002		econstructed		plugged	under my jurist	AUGUST GITU
		ne best of my l	-		2/2002	
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/12/2003						
under the business name of Harp Well & Pump Service Inc. by (signature) Jodd S. Jarp						