WATER WELL RECORD F	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION SE SE NW SE	SECTION NUMBER	ł	RANGE NUMBER
Sedgwick Distance and direction from nearest town or city street address of well if located within city?	1/4 3	T 27 S	R 2E E/W
127th E. & 21st N., 3/8 mile North then West 1/4 mile Wichita, Kansas			
2 WATER WELL OWNER: ATKINSON, Steve			
RR#,ST. ADDRESS,BOX #: 12313 Asbury Circle AYESBURY		Board of Agr	iculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nur	nber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 10	3 ft.	ELEVATION:	
WITH AN "X" IN SECTION BOX: N Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 40	FT. BELOW LAND SU	RFACE MEASURED ON mo/	day/yr: 12/5/03
Pump test data: Well wat	er was	ft. after hours	s of pumping @ gpm
Est. Yield: gpm Well wa Bore Hole Diameter 12 in.			s of pumping @ gpm
	to 103 ft.	and in.	to ft.
	ter supply 7. Lawn a	nd garden only 9. Dewater	ng 11. Injection well 12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field w		ditioning 10. Monitori	ng well
S Was a chemical/bacteriological sample submitted to 0			what mo/day/yr was sample
submitted	Was W	/ater Well Disinfected?	YES NO
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 5. Wrought Iron 7. Fiberglass	Other (Specify	below) CASING JOINTS:	
2, PVC 4, ABS 6. Asbestos-Cement 8. Concrete to	le 50e-26		Welded Clamped
Blank casing diameter 5 in. to 63 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 24 in., Weight:	2.35 lbs. / ft.	Wall thickness or gau	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	Asbestos-Cen	nent 12. None used (open	hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 63 ft. to	103 ft.,	From ft.	to ft.
From ft, to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	103 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other bent	onite hole plug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination: 1. Sentic tank 4. Lateral lines 7. Pit privy	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
1. Septic tank 4. Lateral lines	1. Fuel storage	_	16. Other (specify below)
2. Sewer lines 5. Cess Pool 5. Cess Pool 14. Abandon water wen			
3. Watertight sewer line 6. Seepage pit 9. Feed yard Direction from well? South	2. Pertilizer Storage	How many feet? 15	
From To LITHOLOGIC LOG	From To		OGIC LOG
0 3 topsoil			
3 10 clay			
10 75 tan shale			
75 90 gray shale 90 100 gypsum-gray shale			
90 100 gypsum-gray shale 100 103 limestone			
		www.	
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and			
was completed on (mo/day/year) 12/05/2003 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/08/2003			
under the business name of Harp Well & Pump Service Inc. by (signature)			
,		Jodd D.	Na r n