

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>SW 1/4 NW 1/4 NE 1/4</u>	<u>15</u>	T <u>27</u> S	R <u>20</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>814 White Tail Ct; Wichita, KS</u>					
2 WATER WELL OWNER: <u>Brett Staer</u>					
RR#, St. Address, Box # : <u>814 White Tail Ct.</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : <u>Wichita, KS</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>75</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>27</u> ft. 2 <u>27</u> ft. 3 <u>27</u> ft.			
		WELL'S STATIC WATER LEVEL <u>27</u> ft. below land surface measured on mo/day/yr <u>2.16.04</u>			
		Pump test data: Well water was <u>27</u> ft. after <u>27</u> hours pumping <u>27</u> gpm			
		Est. Yield <u>27</u> gpm: Well water was <u>27</u> ft. after <u>27</u> hours pumping <u>27</u> gpm			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 <u>Domestic (lawn & garden)</u> 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u> </u> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u> </u> No <u> </u>					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u> </u> 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u> </u> 7 Fiberglass Threaded <u> </u>					
Blank casing diameter <u>5</u> in. to <u>75</u> ft. Dia <u>75</u> in. to <u>75</u> ft. Dia <u>75</u> in. to <u>75</u> ft.					
Casing height above land surface <u>1.4</u> in., weight <u>1.60</u> lbs./ft. Wall thickness or gauge No. <u>26</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 7 <u>PVC</u> 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) <u> </u> 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 <u>Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) <u> </u>					
SCREEN-PERFORATED INTERVALS: From <u>65</u> ft. to <u>75</u> ft. From <u> </u> ft. to <u> </u> ft.					
GRAVEL PACK INTERVALS: From <u>25</u> ft. to <u>75</u> ft. From <u> </u> ft. to <u> </u> ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other <u> </u> Grout Intervals: From <u>4</u> ft. to <u>25</u> ft. From <u> </u> ft. to <u> </u> ft. From <u> </u> ft. to <u> </u> ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 <u>Watertight sewer lines</u> 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) <u> </u> 13 Insecticide storage					
Direction from well? <u>South</u> How many feet? <u>50'</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>2</u>	<u>TOPSOIL</u>			
<u>2</u>	<u>13</u>	<u>Clay</u>			
<u>13</u>	<u>21</u>	<u>Green Shale</u>			
<u>21</u>	<u>29</u>	<u>Blue Shale</u>			
<u>29</u>	<u>31</u>	<u>Red Shale</u>			
<u>31</u>	<u>75</u>	<u>Blue Shale</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>2.16.04</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>611</u> This Water Well Record was completed on (mo/day/yr) <u>2.16.04</u> under the business name of <u>Chase Drilling</u> by (signature) <u>Rick Chase</u>					