		WATER WE	ELL RECC	DRD F	orm WV	VC-5 K	(SA 82a-	1212				
1 LOCATION OF WATE	ER WELL:	FRACTION			SECTION NUMBER				RA	RANGE NUMBER		
Sedgwick		NE 1/4	SE 1/4		1/4	4	Т	27 s	R	<u> 2E</u>	E/W	
Distance and direction from	•			•		Wichit	Kansas					
1/4 mile North of 21st St. North & West of Greenwich Road Wichit, Kansas 2 WATER WELL OWNER: LATHAM, George												
RR#,ST. ADDRESS		N. Market						Board of	f Agriculture, Divisi	ion of Wat	ter Resource	
CITY,	STATE: Wich	hita, Kansas			ZI	P CODE:		Application	Number:			
3 LOCATE WELL'S L	OCATION 4	DEPTH OF COMPL	ETED WELL:	10	0 ft.		ELEVATIO	ON:				
WITH AN "X" IN SE		pth of groundwater	Encountered:		ft.			ft.			ft.	
	WI	ELL'S STATIC WAT	TER LEVEL	20	FT. BELO	W LAND S	URFACE ME	EASURED ON 1	no/day/yr:	6/14/0)4	
NW	NE		ip test data:	Well wat			ft. afte		ours of pumping	-	gpm	
w Mile		Est. Yield: Bore Hole Diameter	gpm 12	Well wat in.	ter was to 1	. 00 ft	ft. afte		ours of pumping		gpm ft.	
- "	' ! !	ELL WATER TO BE		111.	10 1	i de la	. and			to 1. Iniecti		
sw	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below 12. Other (Specify below 12. Other (Specify below 13. Other (Specify below 14. Other (Specify below 15. Other (Specify below											
		•		Oil field w			nditioning		toring well			
s		Vas a chemical/bacterion	ological sample s	submitted to D	Department?	YES Was V	NO Nater Well D		es, what mo/da	ay/yr wa: NC		
5 TYPE OF CAS	SING USED:	F 14/22	7		9.0	ther (Specify		CASING JOINT	rs: Glued	т	hreaded	
1. Steel	3. RPM (SF	,		Fiberglass	SDI	R-26	y ocion,	0/10/110/00/111	Welded		Clamped	
2. PVC	> 4. ABS	6. Asbestos-		Concrete til	le 5D	K-20						
Blank casing diamet	er 5		10 ft.,	Dia.	in.	to	ft.,	Dia.	in. 1	to	ft.	
Casing height above		12 in.,	٧	Veight:	2.35 II	os. / ft.	W	all thickness or o	gauge No.	.214		
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)												
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)												
SCREEN OR PERFO		GS ARE:		, ,				, ,				
1. Continuous slo		_	auzed wrappe	ed	7. To	rch cut	9.	Drilled holes	11. No	one (op	en hole)	
2. Louvered shutte	er 4. Key pı		/ire wrapped		(8. Sa	w cut	10.	Other (specify))			
SCREEN - PERFORA		From	40 ft.	to	100		From					
SOREER TERROR	ATION INTERVAL	From	ft.	to	100	ft., ft.,	From	ft. ft.		to	ft. ft.	
GRAVEL PA	ACK INTERVALS:	From	24 ft.	to	100	ft.,	From	ft.		to to	ft.	
		From	ft.	to		ft.,	From	. 1t.		to	ft.	
6 GROUT MATER	IALS: 1 Nort	cement	2. Cement (B. Bentonite			entonite hol			
Grout Intervals:	From 4	ft. to	24 ft.,	From	60 ft.	to	63 ft.		ft.	to	ft.	
What is the nearest s		7	Dit privat	1	0. Livestoc					well/Gas		
1. Septic tank	4. Latera		Pit privy		1. Fuel sto			secticide stora	40.04		cify below)	
2. Sewer lines	5. Cess F	-	Sewage lago			•	14. AL	oandon water w	/eli	o. (opoc	my below,	
Oirection from well?	er line 6. Seepa East	ge pit 9.	Feed yard	'	2. Fertilize	rstorage	Ho	w many feet? 1	15			
From To		LITHOLOGIC	LOG		From	То	Γ		LOGIC LO	G		
0 4	topsoil											
4 25	clay											
25 50 50 55	shale very fine shal	le narticals										
55 85	shale	e particais										
85 100	limestone											
	 											
												
7 Contractor's or	Landowner's Certific	cation: This water w	vell was 1.Cc	onstructed) 2. re	constructed	d or 3.	plugged	under my ju	nisdiction	n and	
was completed on (mo/day/year) 6/14/2004 and this record is true to the best of my knowledge and belief.												
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/16/2004												
under the business	лапо о пагр	wen & rump	Sei vice in	·.	Dy (Si	g. 10.010)		Jo d d	S. Harp			