	WATER WELL REC	CORD Form	WWC-5	KSA 82a-121	2		
1 LOCATION OF WATER WELL:	FRACTION		SECTION NUM			RANGE NUM	BER
Sedgwick		1/4 NW 1/4	11	Т 2'	7 s	R 2E	E/W
	or city street address of well if located with	nin city?					
	Wichita, Kansas						
	HUEBBER 1918 Peckham				Board of Agric	culture, Division of Wat	er Resource
	Wichita, Kansas		710 0005		Analisation Numb	h.a	
3 LOCATE WELL'S LOCATION	4 DEPTH OF COMPLETED WEI	11: 82	ZIP CODE ft.	ELEVATION:	Application Numb	Der.	
WITH AN "X" IN SECTION BOX:		 .		ELEVATION.			
l	Depth of groundwater Encountere	20	ft.		ft.	= (0.1 (6	ft.
	WELL'S STATIC WATER LEVEL			SURFACE MEASU		• •	
NW NE	Pump test data: Est. Yield: gpm			ft. after		of pumping @	gpn
W W E	Est. Yield: gpm Bore Hole Diameter 12	Well water wa in.	to 82	ft. after ft. and	in.	of pumping @ to	gpm ft.
	WELL WATER TO BE USED AS		10 02	it. allu		44 1-141	
swse	1. Domestic 3. Feedlot		ipply 7. Lav	vn and garden only	> Dewaterin	12. Other (Spe	
	2. Irrigation 4. Industrial	6. Oil field water s	supply 8. Air	conditioning	10. Monitoring	g well	
s	Was a chemical/bacteriological samp	ele submitted to Departn				hat mo/day/yr was	-
51 7/75 05 040110 11050	submitted		Wa	as Water Well Disinf	ected?	YES NO)
TYPE OF CASING USED: 1. Steel 3. Rf	PM (SR) 5. Wrought Iron	7. Fiberglass	9. Other (Spe	cify below) CAS	ING JOINTS: C		hreaded
2. PVC 4. AI		8. Concrete tile	SDR-26			Welded C	Clamped
	5 in. to 42 ft.,	Dia.	in. to	ft.,	Dia. ir	n. to	ft.
Casing height above land surface	12			,			16.
TYPE OF SCREEN OR PERFOR	,	Weight: 2.35	b lbs. / ft.	wall th	ckness or gauge	e No214	
1. Steel 3. Stainless S		7. PVC	9. ABS	11. Oti	ner (specify)		
2. Brass 4. Galvanized		8. RMP (SR)	10. Asbestos-		ne used (open h	nole)	
SCREEN OR PERFORATION OF		. ,				,	
	Mill slot 5. Gauzed wrap	nned	7. Torch cut	9 Drill	ed holes	11. None (ope	en hole)
							,
	Key punched 6. Wire wrappe		8. Saw cut	10. Otne	er (specify)		
SCREEN - PERFORATION INTER	RVAL From 42 ft.	. to	82 ft.,	From	ft.	to	ft.
	From ft	. to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVA	ALS: From 24 ft.	. to	82 ft.,	From	ft.	to	ft.
	From ft.	. to	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1.	Neat cement 2. Cemer	nt Grout	3. Bentor	nite	Other bento	nite hole plug	
Grout Intervals: From	4 ft. to 24 ft.,			o ft.,	From	ft. to	ft.
What is the nearest source of poss	sible contamination:	,					
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livesto				13. Insecti	cide storage	15. Oil well/Gas	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)							
	Seepage pit 9. Feed yard	12. Fe i	rtilizer storage				
Direction from well? East	LITUOLOGICLOG	1 -		How ma	ny feet? 15	0.01.00	
From To	LITHOLOGIC LOG	Fr	om To		LITHOLO	GIC LOG	
0 4 topsoil 4 10 clay							
10 70 shale							
70 82 limeston	e						
				<u> </u>			
						· · · · · · · · · · · · · · · · · · ·	
7 Contractor's or Landowner's	Certification: This water well was 1.C	constructed 2	reconstruc	ted or 3.	lugged u	nder my jurisdiction	and
was completed on (mo/day/year	r) 7/21/2004 ar	nd this record is true	to the best of	my knowledge and b	elief.		
Kansas Water Well Contractor's	••			ited on (mo/day/year		2004	
			•				
under the business name of Harp Well & Pump Service Inc. by (signature)							