WATER WEL	L RECORD Fo	orm WW0	C-5 KS	SA 82a-1212	2		
1 LOCATION OF WATER WELL: FRACTION			N NUMBER	TOWNSHIP		RANGE NUMBER	
	SE 1/4 SW	1/4	11	т 27	S	R 21	E/W
Distance and direction from nearest town or city street address of well if located within city? 13224 Glencreek Wichita, Kansas							
2 WATER WELL OWNER: BENNETT, Roger							
RR#,ST. ADDRESS,BOX #: 13224 Glencreek					Board of Agriculture, Division of Water Resource		
CITY, STATE: Wichita, Kansas		ZIP	CODE:		Application Num	ber:	
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLE	TED WELL: 75	ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX: N Depth of groundwater Er	ncountered:	ft.			ft.		ft.
WELL'S STATIC WATE	R LEVEL 25	FT. BELOW	LAND SUF	RFACE MEASUF	RED ON mo/d	ay/yr: 7/21	/04
NW	test data: Well wate	er was		ft. after	hours	of pumping @	gpm
Est. Yield: Bore Hole Diameter	gpm Well water			ft. after	hours	of pumping @	gpm
	12 in.	to 75	ft.	and	in.	to	ft.
WELL WATER TO BE U		er supply <	7. Lawn ar	nd garden only	9. Dewaterir	'8	ction well
2. irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well							
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample							
submitted Was Water Well Disinfected? YES NO							
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded Clamped							
1. Steel 3. RPM (SR) Welded Clamped 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26							
Blank casing diameter 5 in. to 35	5 ft., Dia.	in.	to	ft., D	ia. i	n. to	ft.
Casing height above land surface: 12 in.,				•			
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)							
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)							open hole)
2. Louvered shutter 4. Key punched 6. Wir	re wrapped	8. Saw	cut	10. Other	(specify)		
SCREEN - PERFORATION INTERVAL From	35 ft. to	75	ft.,	From	ft.	to	ft.
From	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS: From	24 ft. to		ft.,	From	ft.	to	ft.
From	ft. to		ft.,	From	ft.	to	ft.
T							
1. Ideat contents 2. Contents of the 1. Sentents in the programme in the p							ug ft.
What is the nearest source of possible contamination:	,						
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well							
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)							
O. Water tight sewer line	eed yard 12	2. Fertilizer s	storage				
Direction from well? Northwest From To LITHOLOGIC	100	Erom T	То	How mar	y feet? 85 LITHOLO	GIC L OG	
0 3 topsoil	<u>-00</u>	From	-10-1		LITHOLO	GIC LOG	
3 8 clay							
8 35 tan shale							
35 60 gray shale							
60 75 gypsum-gray shale			-				
						The state of the s	
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and							
was completed on (mo/day/year) 7/21/2004 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236	This water well	Il record was	completed	on (mo/day/year)	7/23	/2004	
under the business name of Harp Well & Pump Service Inc. by (signature)							
Taip wenter ump	, U. 1100 IIIO	, 13	,	Jo	dd Δ .	Harn	