WATER WELL RECORD	Form WV	NC-5 K	SA 82a-12 <sup>2</sup>	12		
1 LOCATION OF WATER WELL: FRACTION		TION NUMBER				
Sedgwick NE 1/4 SE 1/4 S Distance and direction from nearest town or city street address of well if located within city?	SW 1/4	11	T 2	7 S	R 21	E E/W
13408 Edgewood Drive						
2 WATER WELL OWNER: CENTER, Ron						
RR#,ST. ADDRESS,BOX #: 13408 Edgewood Drive				Board of Agric	culture, Division of V	Vater Resource
CITY, STATE: Wichita, Kansas		IP CODE:		Application Num	ber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	<b>77</b> ft.		ELEVATION:			
Depth of groundwater Encountered:	ft			ft.		ft.
WELL'S STATIC WATER LEVEL 40		)W LAND SU	RFACE MEASU			
, ,,,	ell water was ell water was		ft. after ft. after		of pumping @ of pumping @	gpm gpm
Est. Yield: gpm We		77 ft.	and	in.	to	ft.
WELL WATER TO BE USED AS:				9 Dewaterin	ng 11. Inje	ction well
	ic water supply				12. Other (S	pecify below)
2. Irrigation 4. Industrial 6. Oil fie  Was a chemical/bacteriological sample submitte	eld water supply	y 8. Air cond YES	ditioning	10. Monitorin	ı <b>g well</b> vhat mo/day/yr v	was sample
submitted	su to Department?		/ater Well Disini			NO
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberg	olass 9. C	Other (Specify	below) CAS	ING JOINTS: (	Glued	Threaded
1. Steel 3. RPM (SR)	CD.	R-26			Welded	Clamped
2.FVC 4.Ab3		4-	4	D:		
16		to	•		n. to	ft.
Casing height above land surface: 16 in., Weight: TYPE OF SCREEN OR PERFORATION MATERIAL:	: <b>2.35</b> I	lbs. / ft.	Wall th	ickness or gaug	e No214	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. A	\BS	11. Ot	ner (specify)		
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (	SR) 10. /	Asbestos-Cerr	nent 12. No	ne used (open	hole)	
SCREEN OR PERFORATION OPENINGS ARE:						
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. <b>T</b> c	orch cut	9. <b>Drill</b>	ed holes	11. None (	open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	(8. Si	aw cut	10. Oth	er (specify)		
SCREEN - PERFORATION INTERVAL From 25 ft.	to 77	ft.,				
From ft.	to //	π., ft.,	From From	ft.	to	ft.
GRAVEL PACK INTERVALS: From 24 ft.	to 77	ft.,	From	ft. ft.	to to	ft.
From ft.	to	ft.,	From			ft.
C CROUT MATERIALS				ft. Other hente	onite hole pl	ft.
	om ft.	3. Bentonite	ft.,	From	ft. to	ug ft.
What is the nearest source of possible contamination:						
, 4. Lateral miles						
2. Sewer lines 5. Cess Pool 8. Sewage lagoon	11. Fuel sto	-	14. Aband	on water well	16. Other (sp	ecify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard Direction from well? North	12. Fertilize	r storage		100		
From To LITHOLOGIC LOG	From	ТоТ	How ma	Iny feet? 100 LITHOLO	CIC I OG	
0 4 topsoil	- FIOIII	<del>                                     </del>		LITHOLO	GIC LOG	
4 10 clay						
10 77 shale						
	<del>  ·</del>	<del> </del>				
		<del>  </del>			ECEN/	
					RECEIVE	<del>-U</del>
				N	CT 0 4 20	0.4
	<u> </u>	++			CI U 4 ZU	U4
		+		BURI	EAU OF W	ATER
		1				
7		<u> </u>				
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and						
was completed on (mo/day/year) 9/10/2004 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/13/2004						
under the business name of Harp Well & Pump Service Inc. by (signature)						