Form WWC-5 WATER WELL RECORD KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NW 1/4 Sedgwick NW**1**28 1/4 27 2ES R E/W 1/4 Distance and direction from nearest town or city street address of well if located within city? 21st North and Rock Road, SE corner Wichita, Kansas WATER WELL OWNER: EAROUG, Dr. FARHOUD Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 2102 N. Keeneland Wichita, Kansas CITY, STATE: Application Number: 70 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft Depth of groundwater Encountered: ft. 20 WELL'S STATIC WATER LEVEL 9/10/04 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm -NW NE-Est. Yield: Well water was ft. after hours of pumping @ gpm <u>a</u> gpm ≌ 12 70 Bore Hole Diameter in. and ft. WELL WATER TO BE USED AS: 11. Injection well 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES) 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter in. 25 Dia. ft., Dia. ft. 16 Casing height above land surface: in., 2.35 Weight: lbs / ft Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9 ABS 3. Stainless Steel 1. Steel 5. Fiberglass 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 25 ft. 70 ft., From From to ft to ft. From to ft., From ft. 24 GRAVEL PACK INTERVALS: ft. to 70 From ft., From ft. From ft. to From ft. ft. to **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: 4 24 ft., From ft ft. From to ft., What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit Direction from well? South How many feet? 15 From To LITHOLOGIC LOG From LITHOLOGIC LOG To topsoil clav 15 shale limestone 68 68 shale RUREAU OF WATER under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged 9/10/2004 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/13/2004 under the business name of Harp Well & Pump Service Inc. by (signature) 50 d d 5. 4 rp