Form WWC-5 KSA 82a-1212 WATER WELL RECORD LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NW 1/4 Sedgwick NW1/4 1/4 2 Т 27 s R 2367 E/W Distance and direction from nearest town or city street address of well if located within city? Peckham & Camden, & 1/4 mile East on Northside Wichita, Kansas TWENTY FIRST GROWTH LLC WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 345 N. Riverview, Suite 100 Andover, Kansas CITY, STATE: ZIP CODE: Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 98 ft. **ELEVATION:** Depth of groundwater Encountered: ft. ft. ft WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 8/31/04 Pump test data: Well water was ft. after hours of pumping @ apm MW NE Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 to 98 Σ and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE-1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES submitted Was Water Well Disinfected? TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 4. ABS 2. PVC 5 38 Blank casing diameter to ft.. Dia. ft., Dia to in. ft. to 12 in., Weight: 2.35 Casing height above land surface: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 98 ft From to From ft. to From ft. to ft.. From ft. **GRAVEL PACK INTERVALS:** 24 98 From ft., From ft. ft. ft. From to ft.. From ft. to **GROUT MATERIALS:** 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: 4 ft. 24 From ft., From to ft., ft. From What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 2. Sewer lines 5. Cess Pool 14. Abandon water well 3. Watertight sewer line 6. West 9. Feed yard 12. Fertilizer storage 6. Seepage pit How many feet? 80 Direction from well? From LITHOLOGIC LOG LITHOLOGIC LOG То From To 0 topsoil 4 10 clay 10 70 shale 70 98 lime to shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 8/31/2004 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/3/2004

by (signature)

Jodd S. Harp

under the business name of Harp Well & Pump Service Inc.