WATER WELL RECORD F	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER	1	RANGE NUMBER
Sedgwick NE 1/4 NW 1/4 NW Distance and direction from nearest town or city street address of well if located within city?	1/4 11	T 27 S	R 2E E/W
1/4 mile East of 127th E. & 1/4 mile S. of 21st St. N. (Reed's Cove) Wichita, Kansas			
2 WATER WELL OWNER: RITCHIE DEVELOPMENT PD# ST APPRESS POX # 9100 F 22 and N Plant #1000 Board of Agriculture, Division of Water Resource			
RR#,51. ADDRESS,BOX #: 8100 E. 22nd N. BIVG. #1000			
CITY, STATE: Wichita, Kansas 3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL 70			nber:
WITH AN "X" IN SECTION BOX:	-	ELEVATION:	ft.
Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 20	ft.	ft. IRFACE MEASURED ON mo/o	010101
Pump test data: Well wat			s of pumping @ gpm
			s of pumping @ gpm
Est. Yield: gpm Well wat Bore Hole Diameter 12 in.	to 70 ft.	and in.	to ft.
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public wa	ter supply 7. Lawn a	9. Dewateri	•
1. Domestic 3. Feediot 5. Public water supply 6. Lawl and garden only 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well			
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO			
5 TYPE OF CASING USED: 5 Wrought Iron 7 Fiberglass			Glued Threaded
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	9. Other (Specify	below) CASING JOINTS: (Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete ti	le SDR-26		,
Blank casing diameter 5 in. to 30 ft., Dia.	in. to	ft., Dia.	in. to ft.
1	2.35 lbs. / ft.	Wall thickness or gaug	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)			
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 30 ft. to	70 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	70 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug			
Grout Intervals: From 4 ft. to 24 ft., From	ft. to	ft., From	ft. to ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below			16. Other (specify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard	2. Fertilizer storage		None Apparent
Direction from well?	T- T-	How many feet?	2010 1 00
From To LITHOLOGIC LOG 0 4 topsoil	From To	LITHOLO	OGIC LOG
4 10 clay			
10 57 shale			
57 65 very loose shale 65 80 limestone			
US OU MINESTAGE			
		RE	CEIVED
		SEP	2 4 2004
		BUREAU OF WATER	
		-U1/CM	OCE WATER
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and			
was completed on (mo/day/year) 8/26/2004 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8/30/2004			
under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Jarp			