WATER WELL RECORD Form WWC-5 KSA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP N	
Sedgwick SW 1/4 NE 1/4 SW 1/4 2 T 27	S R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?	
2306 Rosemont Circle Wichita, Kansas	
2 WATER WELL OWNER: MASTERPIECE HOMES	Board of Agriculture, Division of Water Resource
RR#,ST. ADDRESS,BOX #: 15569 SW Butler Road	
	pplication Number:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION:	
WITH AN "X" IN SECTION BOX: N Depth of groundwater Encountered: ft.	ft. ft.
WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURI	ED ON mo/day/yr: 9/24/04
Pump test data: Well water was ft. after	hours of pumping @ gpm
	hours of pumping @ gpm
Est. Yield: gpm Well water was ft. after Bore Hole Diameter 12 in. to 65 ft. and	in. to ft.
V WELL WATER TO BE USED AS:	9. Dewatering 11. Injection well
1. Domestic 3. Feedlot 5. Public water supply 2. Lawn and garden only 12. Other (Specify below)	
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well	
S Was a chemical/bacteriological sample submitted to Department? YES NO	; If yes, what mo/day/yr was sample
submitted Was Water Well Disinfec	ted? YES NO
	G JOINTS: Glued Threaded
1. Steel 3. RPM (SR) SDR-26	Welded Clamped
2. PVC 4. ABS	
Blank casing diameter 5 in. to 35 ft., Dia. in. to ft., Dia	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thick	iness or gauge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Othe	r (specify)
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None	e used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled	holes 11. None ( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other	(specify)
SCREEN - PERFORATION INTERVAL From 35 ft. to 65 ft., From	ft. to ft.
From ft. to ft., From	ft. to ft.
GRAVEL PACK INTERVALS: From 24 ft. to 65 ft., From	ft. to ft.
From ft. to ft., From	ft. to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite O	ther bentonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination:	
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insectici	5
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)	
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage	
Direction from well? West How many	y feet? 100
From To LITHOLOGIC LOG From To	LITHOLOGIC LOG
0 4 topsoil	
4 10 clay	
10 65 shale	
	DEOENJED
	RECEIVED
	0.07 1 0 0001
	OCT 1 9 2004
	BUREAU OF WATER
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and	
was completed on (mo/day/year) 9/24/2004 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year)	9/27/2004
under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Harp	