			WATER WI	ELL REC	ORD I	Form WV	VC-5 K	SA 82a-12	12		
, ,	ON OF WATER	R WELL:	FRACTION			SECT	TION NUMBE	1	P NUMBER	RANGE N	
Sedg			SW 1/4	NW 1/		1/4	11	Т 2	7 s	R 2	E E/W
		n nearest town or city s			n city?						
	N. Peckh		Wichita, NINGHAM, I								
	ER WELL O ADDRESS,		N. Peckham						Board of Agri	culture, Division of	Water Resource
TXIXII,OT.			ita, Kansas		<i>7</i> 1	ZIP CODE: Application Number:					
3 LOCAT	E WELL'S LO	7.1	DEPTH OF COMP	ETED WELL	. 8	2 ft.	OODL.	ELEVATION:			
	N "X" IN SEC	TION BOX:	oth of groundwater			ft.			ft.		ft.
	, N		ELL'S STATIC WA		40			URFACE MEAS		lav/vr 12/1	5/04
	-NW	-NE		np test data:	Well wa		W LAND O	ft. after		of pumping @	gpm
o		NE I	Est. Yield:	gpm		ter was		ft. after		of pumping @	gpm
Wile w		E Bo	ore Hole Diameter	12	in.	to 8	3 2 ft	. and	in.	to	ft.
-	. i		ELL WATER TO B						9. Dewateri	ng 11. Inje	ection well
1	-sw	1						and garden on			pecify below)
			. Irrigation 4. /as a chemical/bacter			vater supply			10. Monitorin	ı g well vhat mo/day/yr	was sample
	s		vas a cnemical/bacter bmitted	lological sample	e submitted to	Department?	YES Was \	NO Water Well Disin		YES	NO
5 TY	PE OF CAS	ING USED:	5 14/m		7	9.0	ther (Specif	v below) CAS	SING JOINTS: (Glued	Threaded
	1. Steel	3. RPM (SR	5. Wrought		7. Fiberglass	, כנט	R-26	, 201011,		Welded	Clamped
	2. PVC	4. ABS	6. Asbestos	-Cement 8	8. Concrete	tile SD	K-20				•
Blank cas	sing diamete	г 5 ч	in. to	42 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing h	eight above	land surface:	12 _{in.,}		Weight:	2.35 II	os. / ft.	Wall th	nickness or gaug	je No214	ļ
TYPE OF	SCREEN C	R PERFORATION	MATERIAL:								
1. Stee	el 3.	Stainless Steel	Fiberglass	_	. PVC	9. A			ther (specify)		
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous slot 3. Mill slot 5. Gauzed wrapped							7. Torch cut 9. Drilled holes 11. None (ope			open hole)	
2. Louve	ered shutte	r 4. Key pu	unched 6. V	Vire wrapped	d .	8. Sa	w cut	10. Oth	er (specify)		
SCREEN -	- PERFORA	TION INTERVAL	From	42 ft.	to	82	ft.,	From	ft.	to	ft.
			From	ft.	to)	ft.,	From	ft.	to	ft.
G	RAVEL PAG	CK INTERVALS:	From	24 ft.	t	o 82	ft.,	From	ft.	to	ft.
			From	ft.	+	0	ft.,	From	ft.	to	ft.
o I GPOI	IT MATERIA	AI S:								onite hole pl	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout Grout Intervals: From 4 ft. to 24 ft., From							3. Bentonite			-	•
		From 4 urce of possible co	ntamination:	,	From	ft.	to	ft.,	From	ft. to	
1. Septic tank 4. Lateral lines 7. Pit privy							livestock pens 13. Insecticide storage			15. Oil well/	
2. Sewe	r lines	5. Cess P	ool 8.	Sewage lag	oon	11. Fuel sto	rage	14. Abanc	ion water well	16. Other (s	pecify below)
3. Wate	rtight sewe	f line 6. Seepag	ge pit 9.	Feed yard		12. Fertilize	r storage				
Direction	from well?	South						How m	any feet? 50 -		
From	То		LITHOLOGIC	LOG		From	То		LITHOLO	GIC LOG	
0		topsoil				+	-				
20		clay shale				-					
	02	SHAIC									
						ļ					
						1					
				·····		+					-
	-		*********			1					
7 -						\ -		<u> </u>	nlungsd	under multi-de-di-	tion and
_		andowner's Certific					constructe			under my jurisdio	aion and
was co	mpleted on (mo/day/year)	12-15-2004	an	d this record	is true to the	best of my	knowledge and	belief.		
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/17/2004											
under the business name of Harp Well & Pump Service Inc. by (signature)											
under the business name of Harp Well & Pump Service Inc. by (signature) Jodd S. Jarp											