

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NW 1/4 SW 1/4 SW 1/4	SECTION NUMBER 14	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 2E E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

12801 Crest Ridge Circle **Wichita, Kansas**

2	WATER WELL OWNER:	HAMMERBACHER	
	RR#,ST. ADDRESS,BOX #:	12801 Crest Ridge Circle	Board of Agriculture, Division of Water Resource
	CITY, STATE:	Wichita, Kansas	Application Number:
		ZIP CODE:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: Depth of groundwater Encountered: _____ ft. WELL'S STATIC WATER LEVEL 60 FT. BELOW LAND SURFACE MEASURED ON 12/1/04 Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm Bore Hole Diameter 12 in. to 95 ft. and _____ in. to _____ ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. <u>Lawn and garden only</u> 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below) Was a chemical/bacteriological sample submitted to Department? YES <u>NO</u> ; If yes, what mo/day/yr was sample submitted _____ Was Water Well Disinfected? <u>YES</u> NO
--	--

5 TYPE OF CASING USED:		1. Steel		3. RPM (SR)		5. Wrought Iron		7. Fiberglass		9. Other (Specify below)		CASING JOINTS: <u>Glued</u>		Threaded			
		2. <u>PVC</u>		4. ABS		6. Asbestos-Cement		8. Concrete tile				Welded		Clamped			
Blank casing diameter		5 in.		to		60 ft.,		Dia.		in.		to		ft.			
Casing height above land surface:		12 in.,		Weight:		2.35 lbs. / ft.		Wall thickness or gauge No.				.214					
TYPE OF SCREEN OR PERFORATION MATERIAL:																	
1. Steel		3. Stainless Steel		5. Fiberglass		7. <u>PVC</u>		9. ABS		11. Other (specify)							
2. Brass		4. Galvanized		6. Concrete Tile		8. RMP (SR)		10. Asbestos-Cement		12. None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:																	
1. Continuous slot		3. Mill slot		5. Gauzed wrapped		7. Torch cut		9. Drilled holes		11. None (open hole)							
2. Louvered shutter		4. Key punched		6. Wire wrapped		8. <u>Saw cut</u>		10. Other (specify)									
SCREEN - PERFORATION INTERVAL		From		60 ft.		to		95 ft.,		From		ft.		to		ft.	
		From		ft.		to		ft.,		From		ft.		to		ft.	
GRAVEL PACK INTERVALS:		From		24 ft.		to		95 ft.,		From		ft.		to		ft.	
		From		ft.		to		ft.,		From		ft.		to		ft.	

6	GROUT MATERIALS:		1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug			
	Grout Intervals:	From	4	ft.	to	24	ft.,	From	ft.	to	ft.,	From	ft.	to
What is the nearest source of possible contamination:														
1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens		13. Insecticide storage		15. Oil well/Gas well				
2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well		16. Other (specify below)				
3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage								
Direction from well? East										How many feet? 40				

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **12/01/2004** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **12/03/2004**

under the business name of **Harp Well & Pump Service Inc.** by (signature) *To dd S. Harp*