

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 NE 1/4 NW 1/4	SECTION NUMBER 23	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 2E E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

414 Gateway Ct.		Wichita, Kansas	
2	WATER WELL OWNER:	RICHARDET, Brian	
	RR#, ST. ADDRESS, BOX #:	414 Gateway Ct.	Board of Agriculture, Division of Water Resource
	CITY, STATE:	Wichita, Kansas	Application Number:
		ZIP CODE:	

N W E S NW NE SW SE X	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION 80X:	
	4 DEPTH OF COMPLETED WELL: 83 ft. ELEVATION:	
	Depth of groundwater Encountered: ft.	
	WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr. 3/20/05	
Pump test data: Well water was ft. after hours of pumping @ gpm		
Est. Yield: gpm Well water was ft. after hours of pumping @ gpm		
Bore Hole Diameter 12 in. to 83 ft. and in. to ft.		
WELL WATER TO BE USED AS:		
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well		
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)		
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted		
Was Water Well Disinfected? YES NO		

5 TYPE OF CASING USED:				9. Other (Specify below)				CASING JOINTS:			
1. Steel		3. RPM (SR)		5. Wrought Iron		7. Fiberglass				Glued	
2. PVC		4. ABS		6. Asbestos-Cement		8. Concrete tile		SDR-26		Welded	
										Threaded	
										Clamped	

Blank casing diameter	5	in.	to	33	ft.,	Dia.	in.	to	ft.,	Dia.	in.	to	ft.
Casing height above land surface:	12	in.,	Weight:	2.35	lbs. / ft.	Wall thickness or gauge No.	.214						

TYPE OF SCREEN OR PERFORATION MATERIAL:

1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)	

SCREEN - PERFORATION INTERVAL	From	33	ft.	to	83	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24	ft.	to	83	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.

6	GROUT MATERIALS:									
	1. Neat cement		2. Cement Grout		3. Bentonite		Other bentonite hole plug			
	Grout Intervals:	From 4 ft.	to 24 ft.,	From	ft.	to	ft.,	From	ft.	to
What is the nearest source of possible contamination:										
1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens		13. Insecticide storage		15. Oil well/Gas well
2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well		16. Other (specify below)
3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage				
Direction from well? South							How many feet? 15			

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 3/20/2005 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/22/2005

under the business name of Harp Well & Pump Service Inc. by (signature) To d d S. Harp