			WATER \	NELL RE	ECORD	Forn	n WV	√C-5 K	(SA 82a-12	12			
1'1	ON OF WATE	R WELL:	FRACTION				SECT	TION NUMBE	R TOWNSH	IP NUMBER	RANGE	NUMBER	
☐ Sedg	wick		SW 1/	4 SW	1/4 NV	V 1/4	4	11	Т 2	27 s	R 2	\mathbf{E} E/W	
Distance an	d direction fro	m nearest town or city	y street address of v	vell if located w	vithin city?								
1823	N. Peckl		Wichita,										
2 WAT	ER WELL (OWNER: SHA	ARP, CRAIC	CONST	RUCTIO	N							
RR#,ST	. ADDRESS	BOX #: 1823	3 N. Peckhar	n Ct.						Board of Agr	iculture, Division of	Water Resource	
CITY, STATE: Wichita, Kansas ZIP CODE:										Application Nun	nber:		
3 LOCAT	E WELL'S LO	OCATION 4	DEPTH OF CO	APLETED W	/ELL:	82	ft.		ELEVATION:			· · · · · · · · · · · · · · · · · · ·	
WITH	AN "X" IN SEC	CTION BOX:	epth of groundwa				ft.			ft.		ft.	
lı 🗁	N		/ELL'S STATIC V						IDEA OF MEAO		41		
	,							W LAND SI		URED ON mo/o		5/05	
	- MM	NE		Pump test da		water wa			ft. after		of pumping @	gpr	
₩ ₩			Est. Yield:	gpm ter 12		water w			ft. after		s of pumping @	gpn	
 		· I I	Bore Hole Diame				to 8	3 2 ft	. and	in.	to	ft.	
	sw		'ELL WATER TO 1. Domestic	3. Feedlot		watere	unnly	7 Lawn	and garden on	9. Dewateri	9	ection well	
	1			4. Industria					nditioning	10. Monitoria		Specify below	
_			z. Imgation Was a chemical/bac					YES	NO		what mo/day/yr	was sample	
	5		ubmitted	teriological sai	ripie subiliitteu	то Берап	unem:		Water Well Disir		YES	NO	
5 TY	PE OF CAS	SING USED:					0.01	hor (Coosifi	, bolow) CA	SING JOINTS: (Glued	Threaded	
_	1. Steel	3. RPM (S	R) 5. Wroug	ht iron	7. Fibergla	ISS		her (Specify	y below) CA	301113. V	Welded	Clamped	
	2. PVC	4 . ABS	6. Asbes	tos-Cement	Concret	e tile	SDI	R-26			Weided	Clamped	
Blank cas	sing diamete	er 5	in. to	42 ft.,	Dia.		in.	to	ft.,	Dia.	in. to	ft.	
	-		24			2.2			•				
"	•	land surface:	,		Weight:	2.3	3 10	os. / ft.	wallt	hickness or gaug	ge No21	4	
		OR PERFORATION S. Stainless Steel			7. PVC		9. AI	ne .	11 0	ther (specify)			
1. Stee			5. Fiberglas			31					h ala)		
2. Bra	SS 4	. Galvanized	6. Concrete	e Tile	8. RMP (SF	<)	10. A	sbestos-Ce	ment 12. N	one used (open	noie)		
SCREEN	OR PERFO	RATION OPENIN	GS ARE:										
1. Continuous slot 3. Mill slot 5. Gauzed wrapped							7. Torch cut			9. Drilled holes 11. None (open hole)			
2. Louve	ered shutte	er 4. Key p	ounched 6	. Wire wrap	ped	(8. Sa	w cut	10. Otł	er (specify)			
SCREEN	DEDECIDA	TION INTERVAL	C	42	ft.	40	82		F				
SCREEN	- PERFORA	TION INTERVAL	From	42		to	04	ft.,	From	ft.	to	ft.	
			From		ft.	to		ft.,	From	ft.	to	ft.	
G	RAVEL PA	CK INTERVALS:	From	24	ft.	to	82	ft.,	From	ft.	to	ft.	
			From		ft.	to		ft.,	From	ft.	to	ft.	
6 GRO	UT MATERI	ALS: 1 Nest	cement	2 Cam	ent Grout		2	Rentonite		Other hent	onite hole p	lua	
Constitute and S. Sentonite										•	U		
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From What is the nearest source of possible contamination:								From	ft. to	o ft.			
1. Septic tank 4. Lateral lines 7. Pit privy							D. Livestock pens 1			ticide storage	15. Oil well	Gas well	
·							1. Fuel storage 14			14. Abandon water well 16. Other (specify below)			
				9. Feed yar	rd .	12. F €	ertilizer	storage					
	rtight sewe	South	ige pit		-				How m	any feet? 18			
From	То		LITHOLOG	IC LOG		ΤF	rom	То	1		GIC LOG		
0	3	topsoil	277770200	10 200		+-	10111			EIIIIOEO	7010 E00		
3	10	clav				\neg							
10	35	tan shale											
35	82	gray shale-gy	nsum										
			· p·······										
									ļ				
						_							
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and													
was completed on (mo/day/year) 4/5/2005 and this record is true to the best of my knowledge and belief.													
under th	ne business	under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Harp											