WATER WELL RECORD Form WWC-5 KSA 82a-1212 SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER LOCATION OF WATER WELL: FRACTION NW 1/4 NW27 2ESedgwick SE 1/4 11 Т R Ε/W Distance and direction from nearest town or city street address of well if located within city? 3/8 mile South & 3/8 mile East of Intersecton of 127th East and 21st St. North Wichita, Kansas RITCHIE DEVELOPMENT WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 8100 E. 22nd St. N. Bldg.1000 CITY, STATE: Wichita, Kansas Application Number: ZIP CODE: 45 4 DEPTH OF CHARGE SOWELL LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: **ELEVATION:** ft Depth of groundwater Encountered: ft. 20 4/11/05 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Well water was ft. after hours of pumping @ Pump test data: gpm NE Mile Est. Yield: Well water was ft. after hours of pumping @ gpm Bore Hole Diamet and ft. WELL WATER USED AS: 11. Injection well 9. Dewatering ·SE-7. Lawn and garden only SW 1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 10. Monitoring well windmill well 2. Irrigation 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) Was Water Well Disinfected? (YES) NO TYPE OF CASING USED: Glued Threaded 9. Other (Specify below) CASING JOINTS: 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped 8. Concrete tile Asbestos-Cement 2. PVC . 4. ABS 6 Dia. ft., Dia in. ft. Blank casing diameter to Casing height appropriete Wall thickness or gauge No. lbs. / ft. Weight: TYPE OF SCREEN OR PERFORATION MATERIAL 11. Other (specify) N/A 7. PVC 9. ABS 3. Stainless Steel 5. Fiberglass 1. Steel 12. None used (open hole) 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) N/A 4. Key punched SCREEN - PERFORATION INTERVAL to ft., From From ft. ft. From to ft., From ft. to ft **GRAVEL PACK INTERVALS:** ft. to ft., From ft From to ft ft. From to ft.. From fŧ to ft. Other bentonite hole plug **GROUT MATERIALS:** 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: ft. ft., 3 to 45 ft. to ft., From What is the nearest source of possible contamination: 13. Insecticide storage 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines None Apparent 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line How many feet? Direction from well? From Τо LITHOLOGIC LOG From Τо LITHOLOGIC LOG cement grout 45 <u>bentonite hole plug</u> Contractor's or Landowner's Certification: This water well was 1, constructed 2. reconstructed or 3. 🤇 plugged under my jurisdiction and 4/11/2005 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year)

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 4/11/2005 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/13/2005

under the business name of Harp Well & Pump Service Inc. by (signature) To dd S. Harp