			WAIERW	ELL RE	CORD	Form WV	VC-5 K	SA 82a-12	12		
111	N OF WATER	R WELL:	FRACTION	~		1	TION NUMBE	1	PNUMBER	RANGE N	
Sedg			SW 1/4		1/4 NW	1/4	11	Т 2	7 s	R 21	E/W
		n nearest town or city s			hin city?						
	N. Peckh		Wichita, I		DICEC IN						
	ER WELL O		CLELLAN F W. 34th St. 1		Kided, in	C.			Board of Agr	iculture, Division of V	Vater Resource
KK#,51.	ADDRESS,		w. 34th St. ita, Kansas	IN.		_	ID 0005		Application No.	-b	
2							IP CODE:	EL EVATION.	Application Nur	nber:	
	E WELL'S LO .N "X" IN SEC	TION BOX:	EPTH OF COM					ELEVATION:			
. —	N		th of groundwate			ft			ft.		ft.
	:	WE	LL'S STATIC W	ATER LEVE	L 25	FT. BELC)W LAND SU	JRFACE MEAS	URED ON mo/o	day/yr: 4/22	2/05
'	-N W	- NE	Pı	ump test data	a: Well wa	ater was		ft. after	hours	of pumping @	gpm
₩ M	1	1	Est. Yield:	gpm	Well w	ater was		ft. after	hours	s of pumping @	gpm
			re Hole Diamete		in.	to	32 ft	. and	in.	to	ft.
-			LL WATER TO						9. Dewateri	ng 11. Inje	ction well
1	-sw	·		. Feedlot			_	and garden on			pecify below)
		1	•	. Industrial		water supply			10. Monitoria	n g well what mo/day/yr v	uae samnla
	S		as a chemical/bacto mitted	eriological sam	ple submitted to	Department?	YES	NO Water Well Disir			NO
5 TV	PE OF CAS		mico							=	
9	l. Steel	3. RPM (SR	5. Wrough	nt Iron	7. Fiberglas	s 9. C	ther (Specify	y below) CA	SING JOINTS:		Threaded
	2. PVC	> 4. ABS	•	s-Cement	8. Concrete	tile SD	R-26			Welded	Clamped
	ing diamete		n. to	42 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
	Ū			42 11.,				•			
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214											
		R PERFORATION		_							
1. Stee		. Stainless Steel	5. Fiberglass		7. PVC	9. A			ther (specify)		
2. Bras	ss 4	. Galvanized	6. Concrete	Tile	8. RMP (SR)	10. <i>A</i>	Asbestos-Ce	ment 12. N	one used (open	hole)	
SCREEN	OR PERFO	RATION OPENING	S ARE:								
1. Conti	nuous slot	3. Mill slo	ot 5.	Gauzed wra	apped	7. T c	rch cut	9. Dri	lled holes	11. None (open hole)
2. Louve	ered shutte	r 4. Key pu	nched 6.	Wire wrapp	ed	(8. Sa	w cut	10. Oth	er (specify)		
									(-,,,		
SCREEN -	PERFORA	TION INTERVAL	From	42	ft. t	o 82	ft.,	From	ft.	to	ft.
			From	1	ft. t	0	ft.,	From	ft.	to	ft.
G	RAVEL PAG	CK INTERVALS:	From	24 f	ft.	to 82	ft.,	From	ft.	to	ft.
			From	f	ft.	to	ft.,	From	ft.	to	ft.
6 GROU	JT MATERIA	ALS: 4 North		2.0						onite hole pl	
<u> </u>		1. 11041.0		• 4	ent Grout		3. Bentonite		belli	•	•
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination:											π.
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well										Gas well	
2. Sewe		5. Cess Po	noi lon	8. Sewage la	agoon	11. Fuel sto	rage	14. Abane	don water well	16. Other (s	pecify below)
				9. Feed yard	_	12. Fertilize	r storane				
	from well?	of line 6. Seepag South	je pit	o. i cou yara	•	12.10111120	Jiorago	How m	any feet? 25		
From	To		ITHOLOGI	CLOG		From	То	1.000.11		OGIC LOG	
0		topsoil	ITTIOLOGI	O LOO		1 10111	 ''	 	LITTIOLC	OIO LOO	
3	8	clav									
8		tan shale	2	V	111.	1	1	.,,,,,			
30		gray shale									
		<u> </u>									
											,
							1				
						+		-			
-1											
7 Conf	tractor's or L	andowner's Certific			Constructe	ed) 2. re	econstructe	d or 3.	plugged	under my jurisdic	tion and
		andowner's Certific	ation: This wate					d or 3.		under my jurisdic	tion and
was cor	mpleted on (4/22/2005		and this record	d is true to th	e best of my		belief.	under my jurisdic	tion and
was cor Kansas	mpleted on (Water Well	(mo/day/year)	4/22/2005 e No. 2	5 236	This water v	d is true to the	e best of my	knowledge and d on (mo/day/ye	belief.	5/2005	tion and