

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1
LOCATION OF WATER WELL:
Sedgwick

FRACTION
SW 1/4 SE 1/4 SW 1/4

SECTION NUMBER
12

TOWNSHIP NUMBER
T 27 S

RANGE NUMBER
R 2E E/W

Distance and direction from nearest town or city street address of well if located within city?

14827 Sport Of Kings
Wichita, Kansas

2
WATER WELL OWNER:
RENNOLET, Clint Construction

RR#,ST. ADDRESS,BOX #:
14827 Sport Of Kings

CITY, STATE:
Wichita, Kansas

ZIP CODE:

Application Number:

3
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4
DEPTH OF COMPLETED WELL:
122 ft.
ELEVATION:

Depth of groundwater Encountered:
ft.

WELL'S STATIC WATER LEVEL
35 FT. BELOW LAND SURFACE MEASURED ON
mo/day/yr:
4/22/05

Pump test data:
Well water was
ft. after
hours of pumping @
gpm

Est. Yield:
gpm
Well water was
ft. after
hours of pumping @
gpm

Bore Hole Diameter
12 in.
to
122 ft.
and
in.
to
ft.

WELL WATER TO BE USED AS:

1. Domestic
3. Feedlot
5. Public water supply
7. Lawn and garden only
9. Dewatering
11. Injection well
12. Other (Specify below)

2. Irrigation
4. Industrial
6. Oil field water supply
8. Air conditioning
10. Monitoring well

Was a chemical/bacteriological sample submitted to Department?
YES
NO

Was Water Well Disinfected?
YES
NO

5
TYPE OF CASING USED:

1. Steel
3. RPM (SR)
5. Wrought Iron
7. Fiberglass
9. Other (Specify below)
CASING JOINTS:
Glued
Threaded

2. PVC
4. ABS
6. Asbestos-Cement
8. Concrete tile
SDR-26
Welded
Clamped

Blank casing diameter
5 in.
to
62 ft.,
Dia.
in.
to
ft.,
Dia.
in.
to
ft.

Casing height above land surface:
12 in.,
Weight:
2.35 lbs. / ft.
Wall thickness or gauge No.
.214

TYPE OF SCREEN OR PERFORATION MATERIAL:

1. Steel
3. Stainless Steel
5. Fiberglass
7. PVC
9. ABS
11. Other (specify)

2. Brass
4. Galvanized
6. Concrete Tile
8. RMP (SR)
10. Asbestos-Cement
12. None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1. Continuous slot
3. Mill slot
5. Gauzed wrapped
7. Torch cut
9. Drilled holes
11. None (open hole)

2. Louvered shutter
4. Key punched
6. Wire wrapped
8. Saw cut
10. Other (specify)

SCREEN - PERFORATION INTERVAL
From
62 ft.
to
122 ft.,
From
ft.
to
ft.

GRAVEL PACK INTERVALS:
From
24 ft.
to
122 ft.,
From
ft.
to
ft.

6
GROUT MATERIALS:

1. Neat cement
2. Cement Grout
3. Bentonite
Other
bentonite hole plug

Grout Intervals:
From
4 ft.
to
24 ft.,
From
ft.
to
ft.,
From
ft.
to
ft.

What is the nearest source of possible contamination:

1. Septic tank
4. Lateral lines
7. Pit privy
10. Livestock pens
13. Insecticide storage
15. Oil well/Gas well

2. Sewer lines
5. Cess Pool
8. Sewage lagoon
11. Fuel storage
14. Abandon water well
16. Other (specify below)

3. Watertight sewer line
6. Seepage pit
9. Feed yard
12. Fertilizer storage

Direction from well?
West

How many feet?
20

From
To
LITHOLOGIC LOG
From
To
LITHOLOGIC LOG

0
3
topsoil

3
8
clay

8
70
tan shale

70
105
gray shale

105
122
gray shale-gypsum-limestone

7
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 4/22/2005 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/25/2005

under the business name of Harp Well & Pump Service Inc. by (signature) J o d d S. Harp