N	V SW NEN	₩WATER	WELL F	RECORD	Forn	n WW	/C-5 K	SA 82a-	1212					
1 LOCATION OF WATE	R WELL:	FRACTION		,			ION NUMBER	1	SHIP NU		RANGE NUM			
Sedgwick			1/4		1/4	4	298	T	24	S	l R	1000	E/W	
Distance and direction from							11		27			2 E		
2057 N. Glenv		YOUNG, E	ita, Kans	as										
	2 WATER WELL OWNER: DEYOUNG, Eric  RR#,ST. ADDRESS,BOX #: 2057 N. Glenwood Ct.  Board of Agriculture, Division of Water Resour													
1		hita, Kans				715	CODE:		Αp	plication No	umber:			
3 LOCATE WELL'S LO		DEPTH OF C		WFII.	82	ft.		ELEVATIO	<u>_</u>					
WITH AN "X" IN SEC	TION BOX:	epth of ground				ft.				ft.			ft.	
l · · · · ·		VELL'S STATIO			ET		W I AND SI	JRFACE ME	A CI IDEI		v/day/vr:	5/3/0		
NW		VELLO STATIC	Pump test		l water w		W LAND 30	ft. after			rs of pumpin		gpm	
	-NE	Est. Yield:	gpr		ll water w			ft. after			irs of pumpin		gpm	
₩ <b>S</b>	E ] I	Bore Hole Dian	0.	12 in.		to 8	<b>2</b> ft.			in.		to	ft.	
-   -		VELL WATER	TO BE USE	O AS:					9	. Dewate	ring 1	1. Injecti	on well	
sw	SE	1. Domestic	3. Feedlo					and garden				her (Spe	cify below	
		2. Irrigation	4. Industr				8. Air cor		10	. Monitor	ring well , what mo/d	avlur wa	e campio	
s		Was a chemical/I ubmitted	bacteriological	sample submitte	d to Depar	tment?	YES Was V	NO Vater Well D	) isinfecte		YES	ayryi wa NC	•	
5 TYPE OF CAS						0.01	her (Specify			JOINTS:	Glued	Т	hreaded	
1. Steel	3. RPM (S	SR) 5. Wro	ought Iron	7. Fiberg	lass			( below)	0.701140	301110.	Welded		Clamped	
2. PVC	4. ABS	6. Asb	estos-Cemei	nt 8. Concre	ete tile	SDF	(-20							
Blank casing diameter	er <b>5</b>	in. to	42	ft., Dia.		in.	to	ft.,	Dia.		in.	to	ft.	
Casing height above	land surface:	<b>12</b> ir	n.,	Weight:	2.3	<b>5</b> lb	s. / ft.	Wa	all thickn	ess or ga	uge No.	.214		
TYPE OF SCREEN	R PERFORATIO	N MATERIAL:												
1. Steel 3	. Stainless Steel	5. Fiberg	lass	7. PVC	)	9. A	38	11	. Other	specify)				
2. Brass 4	. Galvanized	6. Concr	ete Tile	8. RMP (S	SR)	10. As	sbestos-Cer	ment 12	!. None ı	ised (ope	n hole)			
SCREEN OR PERFO	RATION OPENIN	IGS ARE:												
1. Continuous slot	3. Mill s	slot	5. Gauzed	wrapped		7. Tor	ch cut	9. I	Drilled h	oles	11. N	one ( op	en hole)	
2. Louvered shutte	r 4. Key j	punched	6. Wire wr	apped	(	8. Sav	w cut	10.	Other (s	pecify)				
SCREEN - PERFORA	TION INTERVAL	From	42	ft.	to	82	ft.,	From		ft.		to	ft.	
	.,,_,,,,,,,	From		ft.	to		ft.,	From		ft.		to	ft.	
GRAVEL PA	CK INTERVALS:	From	24	ft.	to	82	ft.,	From		ft.		to	ft.	
		From		ft.	to		ft.,	From		ft.				
O COULT MATER	A1 C:								Oth		4 4 - 1	to	ft.	
GROUT MATERIALS: 1. Neat cement 2. Cement Grout							3. Bentonite Other bentonite hole plug							
Grout intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:						ft.	to	ft.	, ł	rom	ft.	to	ft.	
1. Septic tank 4. Lateral lines 7. Pit privy						ivestoci	c pens	13. Insecticide storage 15. Oil well/Gas well						
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16.									II 16. Ot	her (spec	ify below)			
3. Watertight sewe	r line 6. Seep	age pit	9. Feed y	/ard	12. F	ertilizer	storage							
Direction from well?	West							Hov		eet? 12				
From To	0.000	LITHOLO	GIC LOC	3	F	rom	То		L	<u>ITHOL</u>	OGIC LC	G		
0 3	topsoil		-			****								
3 10 10 45	clay tan shale				_		**					-10-		
45 82	gray shale-g	vnsum									****			
		· · · · · · · · · · · · · · · · · · ·												
					_									
					-									
													<del></del>	
										-				
1	L				$\dashv$						-			
<del></del>	andowner's Certi						onstructed		plug		under my j	urisdictio	n and	
was completed on	(mo/day/year)	5/3/20	05	and this red	cord is tru	e to the	best of my	knowledge a	nd belie	f.				
Kansas Water Well	Contractor's Lice	nse No.	236	This water	er well re	cord was	s completed	on (mo/day	/year)	5-0	6-2005			
under the business	name of Harn	Well & Pu	ımp Serv	ice Inc.		by (sig	nature)		7	10	. Har			
	P								<u> Io d</u>	$d \supset$	. Arp	)		