			WATER	WELL RI	ECORD	For	rm WW	/C-5 K	SA 82a-12	12		
1 LOCATIO Sedgy	N OF WATER	RWELL:	FRACTION NW 1/	4 NE	1/4 S	W 1	SECT	ION NUMBER	1	P NUMBER	RANGE N R 21	
		nearest town or city s		•			.,		<u> </u>			
		sgate Ct.		hita, Kar								
	ER WELL O ADDRESS,		CONSTR E. 21st St							Board of Agric	culture, Division of \	Water Resource
	CITY, S		ita, Kansas				ZIF	CODE: 6	7206	Application Num	ber:	
	E WELL'S LO	CATION 4 D	EPTH OF CO	MPLETED V	VELL:	82	ft.		ELEVATION:			
WITH	N N N	Dept	th of groundwa				ft.			ft.		ft.
	!	WE	LL'S STATIC \					W LAND S		URED ON mo/d		1/05
	-NW	- NE	Est. Yield:	Pump test da gpm		ll water Il water			ft. after ft. after		of pumping @ of pumping @	gpm gpm
w Wile	\times	E Bo	re Hole Diame		2 in.		to 8	2 ft		in.	to	ft.
_	sw -	4	LL WATER TO			4	l (7 Lawn	and garden on	9. Dewaterir	'9	ection well
1	SW	"	Domestic Irrigation	 Feedlot Industria 			r supply er supply		nditioning	10. Monitorin		pecify below)
	S	Wa	as a chemical/ba					YES	NO		what mo/day/yr	
EL TV	PE OF CAS		mitted						Water Well Disir		=	NO
٠	. Steel	3. RPM (SR)	5. Wroug	ght Iron	7. Fiberg	glass		her (Specify	y below) CA	SING JOINTS: (Glued Welded	Threaded Clamped
\overline{z}	. PVC	4. ABS	6. Asbes	tos-Cement	8. Concr	ete tile	SDI	R-26			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Blank cas	ing diamete	r 5 i	n. to	42 ft	., Dia		in.	to	ft.,	Dia. i	n. to	ft.
	•	land surface:	24 in.,		Weight:	2.	.35 lb	os. / ft.	Wall t	nickness or gaug	e No214	,
TYPE OF 1. Stee		R PERFORATION Stainless Steel	MATERIAL: 5. Fibergla	ee (7. PVC)	9. AI	BS	11. 0	ther (specify)		
2. Bras	•	Galvanized	6. Concret		8. RMP (\$	SR)		sbestos-Ce		one used (open	hole)	
SCREEN	OR PERFO	RATION OPENING	S ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut									9. Dri	lled holes	11. None (open hole)
2. Louve	ered shutte	4. Key pu	nched	6. Wire wra	pped		8. Sa	w cut	10. Oth	ner (specify)		
SCREEN -	PERFORA	TION INTERVAL	From	42	ft.	to	82	ft.,	From	ft.	to	ft.
			From		ft.	to		ft.,	From	ft.	to	ft.
G	RAVEL PAG	CK INTERVALS:	From	24	ft.	to	82	ft.,	From	ft.	to	ft.
			From		ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout								Bentonite	•	Other bent	onite hole pl	•
Grout Intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:								to	ft.,	From	ft. to	ft.
1. Septic tank 4. Lateral lines 7. Pit privy							Livestock pens 13. Insecticide s			ticide storage	15. Oil well/	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (s										pecity below)		
	rtight sewer	line 6. Seepag South	je pit	9. Feed ya	ard	12.	Fertilizer	storage	Ном п	nany feet? 90		
From	To		ITHOLOG	SIC LOG			From	То	7,000 11	LITHOLO	GIC LOG	
0	3	topsoil										
3		clay						<u> </u>				
10 35		tan shale grav shale										
70		gypsum-brow	n and blac	k shale								
						\dashv		 				
						\dashv						
7 Cont	ractor's or L	andowner's Certific	ation: This wa	ter well was	1. constru	ucted) 2. re	constructe	d or 3.	plugged	under my jurisdic	ction and
was cor	npleted on (mo/day/year)	5/31/200)5	and this re	cord is	true to the	best of my	knowledge and	belief.		
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/31/2005												
under th	under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Harp											
		_								a a a .).	. JVII I'D	