WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER SWSedgwick NE SE 1/4 1/4 11 Т 27 S 2E Ε/W Distance and direction from nearest town or city street address of well if located within city? 1411 N. Glenwood Ct. Wichita, Kansas PARROTINO, Mike WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 519 N. Ridgehurst Wichita, Kansas CITY, STATE ZIP CODE: Application Number: 4 DEPTH OF COMPLETED WELL: ELEVATION: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft ft. ft. Ν 30 7/7/05 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ NE gpm NW Est. Yield: gpm Well water was ft. after hours of pumping @ gpm 12 ≌ Bore Hole Diameter 82 in. ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE 5. Public water supply 7. Lawn and garden only 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? submitted Was Water Well Disinfected? YES NO TYPE OF CASING USED: 5 CASING JOINTS: Glued 9. Other (Specify below) Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 5 30 Dia. Dia. ft. to in. 12 2.35 Casing height above land surface: in.. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 3. Stainless Steel 5. Fiberglass 1 Steel 8. RMP (SR) 2. Brass 4. Galvanized Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 8. Saw cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 10. Other (specify) SCREEN - PERFORATION INTERVAL 30 70 ft.. From to ft. ft. ft. From to ft., From ft. ft. to **GRAVEL PACK INTERVALS:** From 24 ft. to ft., From ft. From ft to ft. From ft. ft. Other **GROUT MATERIALS** 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug 4 Grout Intervals: From ft. 24 ft.. From ft. ft to ft., From What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 6. Seepage pit 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line West How many feet? 10 feet plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τо From Τo 0 3 topsoil 3 10 clav 10 55 tan shale 55 gypsum 65 70 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed under my jurisdiction and or 3. plugged 7/7/2005 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. 236 Kansas Water Well Contractor's License No. This water well record was completed on (mo/day/year) under the business name of Harp Well & Pump Service Inc. by (signature) Jodd S. Harp