WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE NE SE 4 27 1/4 1/4 Т s R 2E E/W Distance and direction from nearest town or city street address of well if located within city? (east well) 2423 N. Greenwich Rd. Wichita, Kansas LATHAM DEVELOPMENT WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 150 N. Market Wichita, Kansas CITY, STATE: Application Number: ZIP CODE: 102 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: **ELEVATION:** Depth of groundwater Encountered: ft. ft. Ħ. N WELL'S STATIC WATER LEVEL 22 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 6/27/05 Pump test data: Well water was NW ft. after hours of pumping @ gpm NE-Est. Yield: <u>e</u> gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 to 102 in ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE 5. Public water supply 7. Lawn and garden only 3. Feedlot 1. Domestic 12. Other (Specify below) 2. Irrigation 6. Oil field water supply 8. Air conditioning 10. Monitoring well 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? YES submitted Was Water Well Disinfected? YES 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter in 32 Dia. ft.. Dia. in. to in ft 12 Casing height above land surface: in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 5. Fiberglass 9 ABS 1 Steel 2. Brass Concrete Tile 8. RMP (SR) 12. None used (open hole) 4. Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 32 102 From ft., From ft. ft. From ft., From ft to ft. **GRAVEL PACK INTERVALS:** 24 ft to 102 From ft., From ft. to ft. From ft. to ft.. From ft. GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3 Bentonite Other bentonite hole plug Grout Intervals: 4 ft 24 From ft., From ft. ft. to ft . From What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines None Apparent 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line Direction from well? How many feet? From Τо LITHOLOGIC LOG LITHOLOGIC LOG From Тο 0 3 topsoil 3 5 clav 5 tan shale 45 102 gynsum-gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or plugged under my jurisdiction and was completed on (mo/day/year) 6/27/2005 and this record is true to the best of my knowledge and belief. 236 Kansas Water Well Contractor's License No. This water well record was completed on (mo/day/year) 7/18/2005 by (signature) under the business name of Harp Well & Pump Service Inc. Jodd S. Harp