WATER WELL RECORD	Form WWC-5 KSA 82a-1212
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER
Sedgwick NW 1/4 NE 1/4 SW	1/4 2 T 27 S R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?	
13203 Mainsgate Ct. Wichita, Kansas	
2 WATER WELL OWNER: MASTERPIECE HOMES	Peaced of Actionalities Districts of Water Pinneyson
RR#,ST. ADDRESS,BOX #: 15569 SW Butler Road	Board of Agriculture, Division of Water Resource
CITY, STATE: Rosehill, Kansas	ZIP CODE: Application Number:
TIDE THE CONTROL TO THE CONTROL OF T	ft. ELEVATION:
WITH AN "X" IN SECTION BOX: N Depth of groundwater Encountered:	ft. ft. ft.
WELL'S STATIC WATER LEVEL 30	FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 8/3/05
Pump test data: Well wa	ater was ft. after hours of pumping @ gpm
1 1	ater was ft. after hours of pumping @ gpm
Est. Yield: gpm Well with Bore Hole Diameter 12 in.	to 70 ft. and in. to ft.
WELL WATER TO BE USED AS:	9. Dewatering 11. Injection well
1. Domestic 3. Feedlot 5. Public w	ater supply 7. Lawn and garden only 12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field	water supply 8. Air conditioning 10. Monitoring well
S Was a chemical/bacteriological sample submitted to	
submitted	Was Water Well Disinfected? YES NO
TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete	tile SDR-26 Welded Clamped
4. AB3	
	in. to ft., Dia. in. to ft.
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft. Wall thickness or gauge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:	44 Other (constitut)
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS 11. Other (specify)
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cement 12. None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut 9. Drilled holes 11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut 10. Other (specify)
SCREEN - PERFORATION INTERVAL From 40 ft. to	o 70 ft. From ft to ft.
From ft. to	- III
GRAVEL PACK INTERVALS: From 24 ft. 1	to 70 ft., From ft. to ft.
From ft.	o ft., From ft. to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite Other bentonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From	ft. to ft., From ft. to ft.
What is the nearest source of possible contamination:	
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon	11. Fuel storage 14. Abandon water well 16. Other (specify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard	12. Fertilizer storage
Direction from well? South	How many feet? 25
From To LITHOLOGIC LOG	From To LITHOLOGIC LOG
0 4 topsoil	
4 15 clay	
15 70 shale	
	· · · · · · · · · · · · · · · · · · ·
Contractor's or Landowner's Certification: This water well was 1. constructe	d 2. reconstructed or 3. plugged under my jurisdiction and
was completed on (mo/day/year) 8/03/2005 and this record	is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8/5/2005	
under the business name of Harp Well & Pump Service Inc.	by (signature) $\int_{0}^{\infty} dd S. \mathcal{A}_{rp}$