		WATER W	ELL RECOR	RD Fo	rm WW	/C-5 K	SA 82a-12	12		
1 LOCATION OF WATER WELL: FRACTION				SECTION NUMBER TOWNSHIP NUMBER			_	RANGE NUMBER		
Sedgwick		SW 1/4	NE 1/4		1/4	2	T 2	7 s	R 2E	E/W
Distance and direction from nearest town or city street address of well if located within city? 13203 Camden Chase Wichita, Kansas										
2 WATER WELL OWNER: GOENTZEL HOMES										
RR#,ST. ADDRESS,BOX #: 1354 S. Ridge Road Board of Agriculture, Division of Water Resource										ater Résource
CITY,	STATE: Wich	ita, Kansas			ZIF	P CODE:		Application Nur	mber:	
3 LOCATE WELL'S LO	OCATION 4	DEPTH OF COMP	LETED WELL:	80	ft.		ELEVATION:			
WITH AN X IN SEC		oth of groundwater	r Encountered:		ft.			ft.		ft.
	WE	ELL'S STATIC WA				W LAND SU	IRFACE MEASI	JRED ON mo/o	day/yr: 8/3 /	05
NW	NE		mp test data:	Well water			ft. after		of pumping @	gpm
W Wile	F B	Est. Yield: ore Hole Diameter	gpm - 12 in	Well wate	rwas to 8	0 ft.	ft. after and	nours in.	s of pumping @	gpm ft.
 	WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well									
sw	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below									ecify below)
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well									
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO										
5 TYPE OF CASING USED: CASING COUNTS: Clund Threaded										
1. Steel 3. RPM (SR) Welded Clamped										
2. PVC 4. ABS 6. Asbestos-Cement 6. Concrete tile										
Blank casing diamete		10	40 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:										
ı	3. Stainless Steel	5. Fiberglass	(7. P)	VC	9. A	BS	11. O	ther (specify)		
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1. Continuous slo	t 3. Mill sle	ot 5. (Gauzed wrapped	d t	7. To i	rch cut	9. Dril	led holes	11. None (o	pen hole)
2. Louvered shutte	er 4. Key pu	unched 6. V	Wire wrapped		8. Sa	w cut	10. Oth	er (specify)		
SCREEN - PERFORA	ATION INTERVAL	From	40 ft.	to	80	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PA	CK INTERVALS:	From	24 ft.	to	80	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATER	IALS: 1. Neat	cement	2. Cement G	rout	3	. Bentonite			tonite hole plu	
Grout Intervals:	From 4	ft. to	24 ft.,	From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible contamination:										
16 Other							16. Other (sp			
2. Sewer lines	5. Cess P	-	. Sewage lagooi		. Fertilizer	•	14. Abanc	lon water well		
Oirection from well?	er line 6. Seepa	ge pit 9.	. Feed yard	12	. Fertilizer	storage	How m	any feet? 25		
From To		LITHOLOGIC	CLOG		From	То	11011111		OGIC LOG	
0 4	topsoil									,-,-
4 20	clay									
20 75 75 80	shale								· ·	
/5	limestone									
			**							
			-11-11							
								**		
	ļ									
		A								
7 Contractor's or	Landowner's Certific	cation: This water	well was 1.Co	nstructed) 2. red	constructed	or 3,	plugged	under my jurisdicti	on and
was completed on		8/03/2005					knowledge and		, ,	
	I Contractor's Licens					-	on (mo/day/yea		/2005	
under the business name of Harp Well & Pump Service Inc. by (signature) $ \int_{0}^{\infty} d d d d d d \int_{0}^{\infty} d d d d d d \int_{0}^{\infty} d d d d d d d d d d d d d d d d d d d$										