

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: <u>Sedgewick</u>		<u>SE</u> $\frac{1}{4}$ <u>NN</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$		<u>24</u>		T <u>27</u> S		R <u>2</u> <u>EW</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>Shadybrook Andover Stagecoach ct (lot 1)</u>									
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources							
RR#, St. Address, Box # :		Application Number:							
City, State, ZIP Code :		<u>Andover, KS 67002</u>							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>80</u> ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. <u>70</u> ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL <u>30</u> ft. below land surface measured on mo/day/yr							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield <u>35</u> gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter <u>10</u> in. to ft., and in. to ft.							
		WELL WATER TO BE USED AS:							
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7</u> Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped <u>2</u> PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded									
Blank casing diameter <u>5</u> in. to ft., Dia. in. to ft., Dia. in. to ft.									
Casing height above land surface <u>12</u> in., weight <u>16.0</u> lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass <u>7</u> PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot <u>3</u> Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From <u>60</u> ft. to <u>80</u> ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>80</u> ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3</u> Bentonite 4 Other									
Grout intervals: From <u>3</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well <u>3</u> Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage									
Direction from well? How many feet? <u>25+</u>									
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0	3	dirt							
3	12	red clay							
12	36	yellow clay							
36	50	shale							
50	80	shale & lime							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. <u>943</u> This Water Well Record was completed on (mo/day/yr)									
under the business name of <u>Reiserer Well Drilling</u> by (signature) <u>Jerry Reiserer</u>									